



SAFETY JOGGER

PROFESSIONAL



Light

DOMINIQUE 01


Stylish Sneakers with Advanced Shock Absorption Technology

DOMINIQUE is a trendy, shock-absorbing sneaker with air cushioning, slip-resistant grip, and breathable comfort for everyday performance.

Upper	Mesh, Action Leather
Lining	3D-Mesh
Footbed	SJ foam footbed
Outsole	PU/Rubber (NBR)
Category	O1 / SR, ESD, FO, HRO
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.400 kg
Norms	EN ISO 20347:2022+A1:2024 ASTM F2892:2024



BLK



Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



SJ Foam

Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Breathable upper

Increased moisture and temperature management for extended wearer comfort.

SAFETY
JOGGER
WORKS

HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com

Industries:
Catering, Cleaning, Food & beverages, Medical

Environments:
Extreme slippery surfaces, Uneven surfaces

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Mesh, Action Leather			
	Upper: permeability to water vapor	mg/cm²/h	21.1	# 0.8
	Upper: water vapor coefficient	mg/cm²	21.6	# 15
Lining	3D-Mesh			
	Lining: permeability to water vapor	mg/cm²/h	42.7	# 2
	Lining: water vapor coefficient	mg/cm²	342.3	# 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	PU/Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm³	81	# 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.38	# 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.39	# 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.29	# 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.32	# 0.22
	Antistatic value	MegaOhm	97.4	0.1 - 1000
	ESD value	MegaOhm	73.6	0.1 - 100
	Heel energy absorption	J	37	# 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com