



Light

## DOMINIQUE 01

**Sneaker with optimal cushioning and comfort**

The DOMINIQUE is a trendy sneaker, providing maximum protection and perfect fit. Features are an air unit, a removable foam footbed for optimal comfort, a slip-resistant outsole and breathable lining.

|               |   |
|---------------|---|
| Upper         | Mesh, Action Leather  |
| Lining        | 3D-Mesh   |
| Footbed       | SJ foam footbed   |
| Outsole       | PU/Rubber   |
| Category      | O1 / ESD, SRC   |
| Size range    | EU 35-48 / UK 3.0-13.0 / US 3.0-13.5<br>JPN 21.5-31.5 / KOR 230-315 |
| Sample weight | 0.410 kg  |
| Norms         | ASTM F2892:2018<br>EN ISO 20347:2012                                |



BLK



### Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



### Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



### SJ Foam

Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.



### SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



### Breathable upper

Increased moisture and temperature management for extended wearer comfort.

**Industries:**

Catering, Cleaning, Food &amp; beverages, Medical

**Environments:**

Extreme slippery surfaces, Uneven surfaces

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

|                | Description                                     | Measure unit          | Result      | EN ISO 20347 |
|----------------|---|-----------------------|-------------|--------------|
| <b>Upper</b>   | <b>Mesh, Action Leather</b>                     |                       |             |              |
|                | Upper: permeability to water vapor              | mg/cm <sup>2</sup> /h | 1.1         | ≥ 0.8        |
|                | Upper: water vapor coefficient                  | mg/cm <sup>2</sup>    | 16.8        | ≥ 15         |
| <b>Lining</b>  | <b>3D-Mesh</b>                                  |                       |             |              |
|                | Lining: permeability to water vapor             | mg/cm <sup>2</sup> /h | 67.9        | ≥ 2          |
|                | Lining: water vapor coefficient                 | mg/cm <sup>2</sup>    | 543         | ≥ 20         |
| <b>Footbed</b> | <b>SJ foam footbed</b>                          |                       |             |              |
|                | Footbed: abrasion resistance (dry/wet) (cycles) | cycles                | 25600/12800 | 25600/12800  |
| <b>Outsole</b> | <b>PU/Rubber</b>                                |                       |             |              |
|                | Outsole abrasion resistance (volume loss)       | mm <sup>3</sup>       | 120         | ≤ 150        |
|                | Outsole slip resistance SRA: heel               | friction              | 0.29        | ≥ 0.28       |
|                | Outsole slip resistance SRA: flat               | friction              | 0.33        | ≥ 0.32       |
|                | Outsole slip resistance SRB: heel               | friction              | 0.21        | ≥ 0.13       |
|                | Outsole slip resistance SRB: flat               | friction              | 0.23        | ≥ 0.18       |
|                | Antistatic value                                | MegaOhm               | N/A         | 0.1 - 1000   |
|                | ESD value                                       | MegaOhm               | 73.6        | 0.1 - 100    |
|                | Heel energy absorption                          | J                     | 36          | ≥ 20         |

Sample size: 41

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.