



#####

DOMINIQUE O1

#####


#####

####, ####, ####
3D-##
SJ#####
PU##
O1 / SR, ESD, #####, HRO
EU 35-48 / UK 3.0-13.0 / US 3.0-13.5
JPN 21.5-31.5 / KOR 230-315
0.400 kg
EN ISO 20347:2022+A1:2024
ASTM F2892:2024



SJ#####
Oxytraction@#####

SRC#SRA+ SRB#####
#####



ESD#
ESD#####

100 KiloOhm## 100 MegaOhm
#####



SJ#####

#####



SRC###
#####1##
SRC### SRA#SRB#####

####



#####



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

#####:
#####, #####, #####, #####

#####:
#####, #####

#####:
#####

#####	#####	##	EN ISO 20347
#####	#####, #####		
	#####	mg/cm ² /h	21.1
	#####	mg/cm ²	21.6
##	3D-#####		
	#####	mg/cm ² /h	42.7
	#####	mg/cm ²	342.3
#####	SJ#####		
	#####	#####	25600/12800
#####	PU/##		25600/12800
	#####	mm ³	81
	##### - #####NaLS - #####	#####	0.38
	##### - #####NaLS - #####	#####	0.39
	SR ##### - ##### - #####	#####	0.29
	SR##### - ##### - #####	#####	0.32
	#####	#####	97.4
	ESD#	#####	73.6
	#####	J	37
			# 20

#####: 42

#####Safety Jogger #####



**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com