



Medium

DUNE OB

High-cut all round desert boot

The robust DUNE safety boots provide SR slip resistance, antistatic properties, breathable comfort, and are equipped with a zipper. They offer body posture pain relief, multiple usages, and hot surface resistance.

Upper Suede Leather, Textile

Lining Mesh

Footbed SJ foam footbed

Outsole Rubber (NBR)

Category OB / SRA, FO, HRO

Size range EU 38-48 / UK 5.0-13.0 / US 5.5-13.5
JPN 24-31.5 / KOR 250-315

Sample weight 0.710 kg

Norms ASTM F3445:2021
EN ISO 20347:2012




SND



Antistatic

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



Breathable upper

Increased moisture and temperature management for extended wearer comfort.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

Industries:

Tactical

Environments:

Dry environment, Uneven surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Description		Measure unit	Result	EN ISO 20347
Upper	Suede Leather, Textile			
	Upper: permeability to water vapor Upper: water vapor coefficient	mg/cm ² /h mg/cm ²	6.0 51	≥ 0.8 ≥ 15
Lining	Mesh			
	Lining: permeability to water vapor Lining: water vapor coefficient	mg/cm ² /h mg/cm ²	49.6 397	≥ 2 ≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm ³	89	≤ 150
	Outsole slip resistance SRA: heel	friction	0.36	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.38	≥ 0.32
	Outsole slip resistance SRB: heel	friction	N/A	≥ 0.13
	Outsole slip resistance SRB: flat	friction	N/A	≥ 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	N/A	≥ 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.


Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

**ENGINEERED
IN EUROPE**
www.safetyjogger.com