



#####


## ECODEMPO S3S LOW

ECODEMPS3L

#####ESD#####

Safety Jogger ECODEMPO S3S#####ESD#####

##### TPU, #####  
## #####  
#### SJ#####  
#### #####  
##### #####/###  
##### #####  
##### S3S / SR, ESD, ESD, ####, #####, #####, HRO  
##### EU 35-48 / UK 3.0-13.0 / US 3.0-13.5  
JPN 21.5-31.5 / KOR 230-315  
##### 0.530 kg  
## EN ISO 20345:2022+A1:2024  
ASTM F2413:2024




#####



#####ESD#  
ESD#####  
###100 KiloOhm##100 MegaOhm  
#####



#####  
#####



#####  
#####  
#####



#####  
#####



#####  
#####



BLK



Proudly ranked in the  
top 1% by EcoVadis  
for sustainability.

#####:  
##, #####, ##, #####

#####:  
####, #####

#####:  
#####

####		####	##	EN ISO 20345
####	TPU, #####			
	#####	mg/cm <sup>2</sup> /h	210.9	# 0.8
	#####	mg/cm <sup>2</sup>	169	# 15
##	#####			
	#####	mg/cm <sup>2</sup> /h	50.38	# 2
	#####	mg/cm <sup>2</sup>	403	# 20
####	SJ#####			
	#####	####	Dry 25600 cycles/Wet 12800 cycles	25600/12800
#####	#####			
	#####	mm <sup>3</sup>	119.4	# 150
	##### - #####NaLS - #####	####	0.48	# 0.31
	##### - #####NaLS - #####	####	0.48	# 0.36
	SR ##### - ##### - #####	####	0.36	# 0.19
	SR##### - ##### - #####	####	0.36	# 0.22
	#####	####	650	0.1 - 1000
	ESD#	####	22	0.1 - 100
	#####	J	25	# 20
#####	#####			
	#####100J#	mm	N/A	N/A
	#####10kN#####	mm	N/A	N/A
	#####200J#	mm	17.5	# 14
	#####15kN#	mm	24.0	# 14

#####:

#####Safety Jogger #####



**HEAD-TO-TOE  
PROTECTION**



Proudly ranked in the  
top 1% by EcoVadis  
for sustainability.

ENGINEERED  
IN EUROPE

[www.safetyjogger.com](http://www.safetyjogger.com)