



#

ECODEMPO S3S LOW

ECODEMPS3L

ESD ##, ## ##

Safety Jogger ##### S3S# ## ## ESD ## #####. ## ## ## #, ## #
##, ## ## #####. ## ## ## ## ## #####.

## ##	TPU, ## ##
## ##	### ##
##	SJ ### # ##
##	## ## ##
## #	###/##
Top	##
####	S3S / SR, ESD, ESD, ##, CI, FO, HRO
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.530 kg
###	EN ISO 20345:2022+A1:2024 ASTM F2413:2024



#####.




ESD# ## ## ## ## ## ## ## ## ##

100##### 100### #####.




#####.



#####. ## ## ## ## ## ## ## ## ##
#####.



##.



##.

**SAFETY
JOGGER**
WORKS

**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

**ENGINEERED
IN EUROPE**

www.safetyjogger.com

##:
####, ###, ##, ##

##:
##, ## #####

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	TPU, ### ##			
	##: ### ###	mg/cm²/h	210.9	# 0.8
	##: ### ##	mg/cm²	169	# 15
## ##	### ##			
	##: ### ###	mg/cm²/h	50.38	# 2
	##: ### ##	mg/cm²	403	# 20
##	SJ ### # ###			
	###: ####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
## #	###/##			
	### #####(## ##)	mm³	119.4	# 150
	## ### ## - ### + NaLS - ## ### #####	##	0.48	# 0.31
	## ### ## - ### + NaLS - ## ## ###	##	0.48	# 0.36
	SR ### ## - ### + ##### - ##### ## ##	##	0.36	# 0.19
	SR ### ## - ### + ##### - ## ## ###	##	0.36	# 0.22
	### ## #	###	650	0.1 - 1000
	ESD #	###	22	0.1 - 100
	#### ## ##	J	25	# 20
Top	##			
	#### ## ##(## # ## 100J)	mm	N/A	N/A
	#### ## ##(## # ## ## 10kN)	mm	N/A	N/A
	#### ## ##(## # ## 200J)	mm	17.5	# 14
	### ## ## ##(## # ## ## 15kN)	mm	24.0	# 14

##:

###, ## ## ##### ### # #####. ## ##### ### Safety Jogger # ##### ###, ### ## ## ##### ## ##### ##### ## # #####.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com