



# SAFETY JOGGER

## INDUSTRIAL

## ECODESERT S1P MID

ECODESERT

## Eco Extra Wide S1P Safety Shoes

ECODSERT #####

#####	#####
#####	#####
#####	SJ #####
#####	#####
#####	PU/PU
#####	#####
#####	S1 P / ####.####, #####
#####	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5
#####	JPN 21.5-31.5 / KOR 230-315
#####	0.662 kg
#####	ASTM F2413:2018
#####	EN ISO 20345:2022



BLK



AHc



KHA



A yellow 'WET FLOOR' caution sign with a 'SRC' logo on the floor.

##### SRC  
#####  
SRC ##### SRA ## SRB



A decorative horizontal border consisting of five parallel lines. The lines are black and have a diagonal hatching pattern running across them from left to right. The spacing between the lines is consistent, creating a repeating pattern of vertical bars.



#####
 #####



```
#####
#####
```



**SJ #**  
#####  
#####  
#####  
#####



## **SJ-3-Fit**

---

---

**SAFETY  
JOGGER  
WORKS**

# HEAD-TO-TOE PROTECTION



Proudly ranked in the  
top 1% by EcoVadis  
for sustainability.

ENGINEERED  
IN EUROPE

[www.safetyvlogger.com](http://www.safetyvlogger.com)

#####:

#####, #####, #####, ##### #####

#####:

#####, #####

#####:####:

#####

#####		#####	#####	EN ISO 20345
#####	#####			
	#####: #####	##./##./##	7.1	# 0.8
	#####: #####	##./##	57.5	# 15
####	#####			
	#####: #####	##./##./##	10.7	# 2
	#####. #####	##./##	87.8	# 20
#####	SJ #####			
	#####: ##### (####/####) (###)	###	Dry 25600 cycles/Wet 12800 cycles	25600/12800

##### PU/PU

##### (#####)	##	Relative volume loss:0.9g/cm <sup>3</sup> (Density:0.98)	# 150
##### - ##### + NaLS - #####	#####	0.48	# 0.31
##### - ##### + NaLS - #####	#####	0.49	# 0.36
SR Slip Resistance - Ceramic + Glycerin - #####	#####	0.21	# 0.19
##### SR - ##### + ##### - #####	#####	0.24	# 0.22
#####	#####	26.5	0.1 - 1000
## ESD	#####	N/A	0.1 - 100
#####	##	40	# 20
#####	##		
##### (##### 100J)	##	N/A	N/A
##### (##### 10kN)	##	N/A	N/A
##### (##### 200J)	##	17.5	# 14
##### (##### 15kN)	##	23.0	# 14

#####:

##### Safety Jogger #####

