

Light

ECONILA S1 LOW

ECONILAS1L

Extra Wide S1 Safety Shoes

ECONILA eco safety shoe with recycled upper, composite toe, slipresistant rubber outsole, ESD protection and extra wide fit for sustainable comfort.


Upper	Knitted Recycled Textile
Lining	Recycled Mesh
Footbed	SJ Memory foam footbed
Midsole	N/A
Outsole	Phylon/Rubber (NBR)
Toecap	Composite
Category	S1 / SR, ESD, FO, HRO
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.429 kg
Norms	ASTM F2413:2018 EN ISO 20345:2022



BLK



KHA




Rubber outsole

Rubber outsoles provide versatile functions that make them suitable for many areas of application: excellent cut resistance, heat and cold resistance, high flexibility at cold temperatures, resistance against oil, fuel and many chemicals.



Composite toe

Metalfree and lightweight, no thermal or electrical conductivity



Metal free

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



Slip resistance (SR)

Replaces the previously used term of SRA+SRB=SRC. SR means the slip test has been executed on tiles contaminated with soap and with oil.



Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.

Industries:

Assembly, Automotive, Logistics, Industry

Environments:

Dry environment, Uneven surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Knitted Recycled Textile			
	Upper: permeability to water vapor	mg/cm²/h	2.3	# 0.8
	Upper: water vapor coefficient	mg/cm²	45	# 15
Lining	Recycled Mesh			
	Lining: permeability to water vapor	mg/cm²/h	34.59	# 2
	Lining: water vapor coefficient	mg/cm²	277	# 20
Footbed	SJ Memory foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	Dry 25600 cycles/Wet 12800 cycles	25600/12800
Outsole	Phylon/Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm³	119.4mm³(Density:1.3)	# 150
	Outsole slip resistance SRA: heel	friction	0.32	# 0.28
	Outsole slip resistance SRA: flat	friction	0.40	# 0.32
	Outsole slip resistance SRB: heel	friction	0.18	# 0.13
	Outsole slip resistance SRB: flat	friction	0.21	# 0.18
	Antistatic value	MegaOhm	215	0.1 - 1000
	ESD value	MegaOhm	14.6	0.1 - 100
	Heel energy absorption	J	25	# 20
Toecap	Composite			
	Impact resistance toecap (clearance after impact 100J)	mm	NA	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	16	# 14
	Compression resistance toecap (clearance after compression 15kN)	mm	17	# 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com