

## Viper Vario



<b>Notified Body</b>	CE 2756		
<b>Article No., EAN &amp; Weight</b>	EL2212063	6425670030630	1,200 grams
<b>Standardization</b>	EN354:2010 EN355:2002	Lanyards Energy absorbers	
<b>Materials used</b>	Line Hooks	12 mm kernmantle rope. Steel safety hook (022 – Kangri). Aluminum scaffolding hooks (426 – Fuji San).	
<b>Description</b>	<ul style="list-style-type: none"> <li> Adjustable safety lanyard with energy absorber;</li> <li> The rope and the energy absorber ensure that the force of the fall is absorbed to a force &lt; 6kN and therefore has an injury-limiting effect;</li> <li> <b>Minimum space under the workplace must be 6.5 meters.</b></li> </ul>		
<b>Length</b>	Adjustable between 1,4 meter and 2 meters		
<b>Maximum workload</b>	100 kg		
<b>Packaging</b>	In a bag, manual included.		
<b>Lifetime</b>	<p>Up to 10 years after first use; up to 12 years after production date. Full body harness of a single user, periodically inspected by experts and recorded in inspection log, carefully handled and maintained, stored in accordance with regulations, not in contact with oil, grease or aggressive chemicals, can be used for up to 10 years. <b>Follow the user manual!</b></p>		