SAFETY JOGGER
INDUSTRIAL

中等

ELEVATE81 S1 P

中帮安全鞋，配备Zone Traction极致摩擦力和Tripguard落地保护。

Safety Jogger's ELEVATE81 safety shoes offer superior grip, protection, and comfort in dry and slippery environments. With SR slip-resistance, steel toecap and midsole, and breathable leather, they're perfect for various industries.

鞋面	耐磨皮革
内里	透气网布
鞋垫	SJ 抗菌防臭海波丽鞋垫
中底	-
鞋头	-
等级	S1 P / SR, FO, HRO
大小范围	EU 37-48 / UK 4.0-13.0 / US 4.5-13.5 JPN 23-31.5 / KOR 240-315
样品重量	0.695 kg
标准	ASTM F2413:2018 EN ISO 20345:2022

BLK

Shoes For Crews
在不同的湿滑路面上行走时，Shoes For Crews安全鞋和职业鞋可提供更强的抓地力、防滑性等。

S1P
在干燥环境工作时，若没有水/液体喷溅的风险，您对鞋的需求便是保护脚趾，防穿刺，以及良好的透气性吧？ 那么您需要S1P安全鞋。

SRC防滑
鞋底防滑是安全鞋和职业鞋最重要的功能之一。 SRC同时通过SRA和SRB鞋底防滑性测试，同时在钢板和陶瓷表面进行测试。

钢制鞋包头
金属支撑十分坚固，保护穿戴者的脚部不受坠落或滚动物体的伤害。

钢制中底
防穿刺钢中底由不锈钢或涂层钢制成，防止尖锐物体穿透大底。

透气皮革鞋面
天然皮革彰显卓越舒适性，经久耐用，用途广泛。

工业:
汽车，化学，清洁，建筑，物流，工业

环境:
极度湿滑表面，干燥环境

维护指南:
建议定期清洁鞋类，并使用适当的产品保养，旨在延长鞋类寿命。 不得将鞋子摆放至暖气片上烘干，不得在热源附近烘干。

	描述	测量单位	结果	EN ISO 20345
鞋面	**耐磨皮革**			
	帮面：水蒸气渗透性	毫克/平方厘米/小时	2.5	大于等于 0.8
	帮面：水蒸气系数	毫克/平方厘米	27.4	大于等于 15
内里	**透气网布**			
	衬里：水蒸气渗透性。	毫克/平方厘米/小时	51.9	大于等于 2
	衬里：水蒸气系数	毫克/平方厘米	415.5	大于等于 20
鞋垫	**SJ 抗菌防臭海波丽鞋垫**			
	脚垫：耐磨性（干/湿）（周期）	转数	25600/12800	25600/12800
鞋头	**-**			
	抗冲击鞋包头（冲击后间隙100J）	毫米	N/A	N/A
	抗压鞋包头（压缩后的间隙为10kN）	毫米	N/A	N/A
	抗冲击鞋包头（冲击后间隙200J）	毫米	15.5	大于等于 14
	抗压鞋包头（压缩后的间隙为15kN）	毫米	19.5	大于等于 14

样品大小: 42

我们的鞋子在不断发展,所有产品名称和品牌Safety Jogger，均已注册，未经我们的书面同意，不得以任何形式使用或复制。