



SAFETY JOGGER

PROFESSIONAL



Medium

ELIS O2

Wide-Fit Sneaker with ESD protection

Elis wide-fit sneakers with SR slipresistant outsole, ESD features and waterrepellent upper deliver comfort and protection.

| | |
|---------------|---|
| Upper | Lorica |
| Lining | 3D-Mesh |
| Footbed | SJ foam footbed |
| Outsole | Phylon/Rubber (NBR) |
| Category | O2 / ESD, SRC |
| Size range | EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310 |
| Sample weight | 0.247 kg |
| Norms | ASTM F2892:2018 EN ISO 20347:2012 |



BLK



WHT



3D mesh

Three-dimensional produced distance mesh to provide increased moisture and temperature management.




Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.




Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



Rubber outsole

Rubber outsoles provide versatile functions that make them suitable for many areas of application: excellent cut resistance, heat and cold resistance, high flexibility at cold temperatures, resistance against oil, fuel and many chemicals.

SAFETY
JOGGER
WORKS

HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com

Industries:
Catering, Cleaning, Medical

Environments:
Dry environment, Extreme slippery surfaces, Wet environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20347 |
|---------|---|--------------|-------------|--------------|
| Upper | Lorica | | | |
| | Upper: permeability to water vapor | mg/cm²/h | 2.18 | # 0.8 |
| | Upper: water vapor coefficient | mg/cm² | 18 | # 15 |
| Lining | 3D-Mesh | | | |
| | Lining: permeability to water vapor | mg/cm²/h | 70 | # 2 |
| | Lining: water vapor coefficient | mg/cm² | 350 | # 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | Phylon/Rubber (NBR) | | | |
| | Outsole abrasion resistance (volume loss) | mm³ | 105 | # 150 |
| | Outsole slip resistance SRA: heel | friction | 0.44 | # 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.48 | # 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.25 | # 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.29 | # 0.18 |
| | Antistatic value | MegaOhm | N/A | 0.1 - 1000 |
| | ESD value | MegaOhm | 60 | 0.1 - 100 |
| | Heel energy absorption | J | 28 | # 20 |

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com