



LIGHTWEIGHT

ELIS 02

Wide comfort fitting occupational sneaker

Upper	Synthetic Leather
Outsole	EVA/Rubber
Toecap	
Midsole	
Lining	3D-Mesh
Footbed	SJ foam footbed
Standards	EN ISO 20347 - O2 / ESD, SRC
Sample weight	220 gr.
Size range	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 / CM 23.0-31.0



3D MESH
Three-dimensional produced distance mesh to provide increased moisture and temperature management.

ELECTROSTATIC DISCHARGE (ESD)
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 35 MegaOhm.

HEEL ENERGY ABSORPTION
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

OXYGRIP / SJ GRIP
Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.

REMOVABLE INSOLE
Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.

RUBBER OUTSOLE
Rubber outsoles provide versatile functions that make them suitable for many areas of application: excellent cut resistance, heat and cold resistance, high flexibility at cold temperatures, resistance against oil, fuel and many chemicals.



LIGHTWEIGHT

ELIS 02

Industries:
Catering, Cleaning, Medical

Environments:
Dry environment, Extreme slippery surfaces, Wet environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.



	Description	Measure unit	Result	EN ISO 20347
Upper	Synthetic Leather			
	Upper: permeability to water vapor	mg/cm ² /h	2.18	≥ 0.8 mg/cm ² /h
	Upper: water vapor coefficient	mg/cm ²	18	≥ 15 mg/cm ²
Lining	3D-Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	70	≥ 2 mg/cm ² /h
	Lining: water vapor coefficient	mg/cm ²	350	≥ 20 mg/cm ²
Footbed	SJ foam footbed			
	Footbed: abrasion resistance	cycles	400	≥ 400 cycles
Outsole	EVA/Rubber			
	Outsole abrasion resistance (volume loss)	mm ³	105	≤ 150 mm ³
	Outsole slip resistance SRA: heel	friction	0.44	≥ 0.28 friction
	Outsole slip resistance SRA: flat	friction	0.48	≥ 0.32 friction
	Outsole slip resistance SRB: heel	friction	0.25	≥ 0.13 friction
	Outsole slip resistance SRB: flat	friction	0.29	≥ 0.18 friction
	Antistatic value	MegaOhm	N/A	0.1 - 1000 MegaOhm
	ESD value	MegaOhm	60	0.1 - 100 MegaOhm
	Heel energy absorption	J	34	≥ 20 J
Toecap	Impact resistance toecap (clearance after impact 100J)	mm	N/A	≥ 13 mm
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	≥ 13 mm
	Impact resistance toecap (clearance after impact 200J)	mm	N/A	≥ 13 mm
	Compression resistance toecap (clearance after compression 15kN)	mm	N/A	≥ 13 mm

*Our shoes are constantly evolving, the technical data above may change.
All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.*

Sample size: 38