

Datasheet

Delta 1



Notified Body	CE 2756		
Article No. EAN, weight	ELVDW1KH1AH20	8719159005515	1,200 grams
	ELVDW1KH1AH201.5	8719159005522	1,100 grams
Standardization	EN354:2010	Lanyards	
	EN355:2002	Energy absorbers	
Materials used	Line	Elasticated webbing, PES fibers, width 36mm, black.	
	Hooks	Steel scaffolding hook (026 – Brooks). Steel connector (223 – Annapurna).	
Description	<ul style="list-style-type: none">  The Delta 1 is an elastic safety lanyard with an energy absorber;  The elasticated, 36 mm wide tubular webbing, ensures that the length of the line is minimized, which can prevent dangerous situations, such as tripping;  Other hooks are available on request;  Minimum space under the workplace must be 6.5 meters. 		
Length	1,5 & 2 meters		
Maximum workload	100 kg Optional Magnum energy absorber from 50 – 150 kg		
Packaging	In a bag, manual included.		
Lifetime	<p>Up to 10 years after first use; up to 12 years after production date.</p> <p>Full body harness of a single user, periodically inspected by experts and recorded in inspection log, carefully handled and maintained, stored in accordance with regulations, not in contact with oil, grease or aggressive chemicals, can be used for up to 10 years.</p> <p>Follow the user manual!</p>		