



EOS S3S

#####ESD#####

Safety Jogger EOS#####

####	#####
##	###
#####	SJ#####
#####	#####
#####	PU/PU
#####	#####
#####	S3 / SR, ESD, #####
#####	EU 35-50 / UK 3.0-14.0 / US 3.0-15.0
#####	JPN 21.5-33.0 / KOR 230-330
#####	0.665 kg
##	ASTM F2413:2018
	EN ISO 20345:2022



S3

S3#####


#####



SRC#####

#####SRC#####SRA#SRB#####

#####




#####ESD#

ESD#####

#####100 KiloOhm#100 MegaOhm

#####



#####

#####

#####



#####

#####

#####



#####

#####

#####



210



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

#####:
#####, ####, #####, ##, ##, #####, ####

#####:
#####, ####, #####, ####

#####:
#####

####	####	##	EN ISO 20345
####	#####		
	#####	mg/cm ² /h	2.0
	#####	mg/cm ²	24.2
##	####		
	#####	mg/cm ² /h	67.6
	#####	mg/cm ²	541
#####	SJ#####		
	#####	####	25600/12800
#####	PU/PU		25600/12800
	#####	mm ³	85.1
	SRA####	####	# 0.28
	SRA####	####	# 0.32
	SRB####	####	# 0.13
	SRB####	####	# 0.18
	####	####	N/A 0.1 - 100
	ESD#	####	24 0.1 - 100
	#####	J	35 # 20
#####	#####		
	#####100J#	mm	N/A N/A
	#####10kN#####	mm	N/A N/A
	#####200J#	mm	16.0 # 14
	#####15kN#	mm	21.5 # 14

#####:

#####Safety Jogger #####



**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com