



Medium

EVA 01

Sporty look, great comfort

The EVA shoes offer unmatched safety and comfort. They feature ESD technology and removable footbed for higher comfort, superior support, and excellent grip. Ideal for various industries.

Upper Action Leather

Lining Mesh

Footbed EVA

Outsole EVA/Rubber

Category O1 / ESD

Size range EU 35-42 / UK 3.0-8.0 / US 5.5-10.5
JPN 21.5-26.5 / KOR 230-270

Sample weight 0.270 kg

Norms ASTM F2892:2018
EN ISO 20347:2022(Europe)



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Coolmax® lining

Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



WHT



BLK



Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.

Industries:

Catering, Cleaning, Food & beverages, Medical, Uniform

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Description		Measure unit	Result	EN ISO 20347
Upper	Action Leather			
	Upper: permeability to water vapor Upper: water vapor coefficient	mg/cm ² /h mg/cm ²	1.3 17.4	≥ 0.8 ≥ 15
Lining	Mesh			
	Lining: permeability to water vapor Lining: water vapor coefficient	mg/cm ² /h mg/cm ²	14.5 116.1	≥ 2 ≥ 20
Footbed	EVA			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	EVA/Rubber			
	Outsole abrasion resistance (volume loss)	mm ³	77	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.52	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.52	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	N/A	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	N/A	≥ 0.22
	Antistatic value	MegaOhm	88	0.1 - 1000
	ESD value	MegaOhm	22	0.1 - 100
	Heel energy absorption	J	29	≥ 20

Sample size: 37

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.


Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

**ENGINEERED
IN EUROPE**
www.safetyjogger.com