

Light

FLOW S1P SANDAL TLS

FL0WS1PSTL

Metal-Free S1P Safety Sandal TLS

FLOW safety sandal with breathable perforated upper, lightweight composite toe cap and slipresistant outsole keeps feet cool, protected and agile.

Upper	Synthetic Nubuck
Lining	3D-Mesh
Footbed	SJ foam footbed
Midsole	Anti-puncture Textile
Outsole	PU/PU
Toecap	Composite
Category	S1 P / ESD, SRC
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.610 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011




TLS (Twist Lock System)

Safety Jogger's innovative TLS closure allows you to quickly tighten and loosen your safety footwear with one hand and under any conditions, even when you are wearing safety gloves. TLS ensures a fast, safe and easy precision fit that offers enhanced comfort and enables you to perform at your best.



3D mesh

Three-dimensional produced distance mesh to provide increased moisture and temperature management.



Breathable, perforated upper

Increased moisture and temperature management for extended wearer comfort in dry working environments.




Composite toecap

Metal-free and lightweight, no thermal or electrical conductivity



BLK



Antistatic

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.

Industries:

Assembly, Automotive, Catering, Logistics

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Synthetic Nubuck			
	Upper: permeability to water vapor	mg/cm²/h	2.2	# 0.8
	Upper: water vapor coefficient	mg/cm²	28	# 15
Lining	3D-Mesh			
	Lining: permeability to water vapor	mg/cm²/h	61	# 2
	Lining: water vapor coefficient	mg/cm²	490	# 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm³	84	# 150
	Outsole slip resistance SRA: heel	friction	0.36	# 0.28
	Outsole slip resistance SRA: flat	friction	0.37	# 0.32
	Outsole slip resistance SRB: heel	friction	0.14	# 0.13
	Outsole slip resistance SRB: flat	friction	0.19	# 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	39	0.1 - 100
	Heel energy absorption	J	27	# 20
Toecap	Composite			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	15.0	# 14
	Compression resistance toecap (clearance after compression 15kN)	mm	19.0	# 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com