



#####

FLOW S1P SANDAL TLS

FLWS1PSTL

TLS#####

FLOW#####

#####FLOW#####

#####ESD#####

#####

3D-####

SJ#####

#####

PU/PU

#####

S1 P / ESD, SRC

EU 35-48 / UK 3.0-13.0 / US 3.0-13.5

JPN 21.5-31.5 / KOR 230-315

0.610 kg

ASTM F2413:2018

EN ISO 20345:2011



TLS#####

Safety Jogger####TLS#####

#####

#####TLS#####

#####


#####



3D####

#####

#####



#####

#####

#####



#####

#####



###

#####

#####100 KiloOhm##1 GigaOhm

#####



#####ESD#

ESD#####

#####

###100 KiloOhm##100 MegaOhm

#####

**SAFETY
JOGGER**
WORKS

**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

**ENGINEERED
IN EUROPE**

www.safetyjogger.com

####:
##, #####, #####, #####, #####

#####:
#####, #####

#####:
#####

	####	####	##	EN ISO 20345
####	#####			
	#####	mg/cm²/h	2.2	# 0.8
	#####	mg/cm²	28	# 15
##	3D-####			
	#####	mg/cm²/h	61	# 2
	#####	mg/cm²	490	# 20
####	SJ#####			
	#####	####	25600/12800	25600/12800
#####	PU/PU			
	#####	mm³	84	# 150
	##### SRA####	####	0.36	# 0.28
	##### SRA####	####	0.37	# 0.32
	##### SRB####	####	0.14	# 0.13
	##### SRB####	####	0.19	# 0.18
	####	####	N/A	0.1 - 1000
	ESD#	####	39	0.1 - 100
	#####	J	27	# 20
#####	#####			
	#####100J#	mm	N/A	N/A
	#####10kN#####	mm	N/A	N/A
	#####200J#	mm	15.0	# 14
	#####15kN#	mm	19.0	# 14

#####.
#####Safety Jogger #####



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com