



Light

## FREEDOM S1PS MID

FYTS1PSMID

### Lightweight Safety Shoes S1PS Mid

Free your toes with FREEDOM S1PS MID. The anatomically shaped toe cap supports barefoot-like walking. Lightweight, breathable and metal free.


Upper	Textile
Lining	3D-Mesh
Footbed	SJ foam footbed
Midsole	Nonwoven
Outsole	ETPU/Rubber (NBR)
Toecap	Nano Carbon
Category	S1 PS / SR, SC, FO, HI, HRO, CI, ESD
Size range	EU 35-50 / UK 3.0-14.0 / US 3.0-15.0 JPN 21.5-33.0 / KOR 230-330
Sample weight	0.585 kg
Norms	EN ISO 20345:2022+A1:2024 ASTM F2413:2024




BLK



**3D mesh**  
Three-dimensional produced distance mesh to provide increased moisture and temperature management.



**Breathable upper**  
Increased moisture and temperature management for extended wearer comfort.



**Rubber outsole**  
Rubber outsoles provide versatile functions that make them suitable for many areas of application: excellent cut resistance, heat and cold resistance, high flexibility at cold temperatures, resistance against oil, fuel and many chemicals.

**Industries:**

Assembly, Automotive, Industry, Logistics

**Environments:**

Dry environment, Extreme slippery surfaces

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
<b>Upper</b>	<b>Textile</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	32.71	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	262	≥ 15
<b>Lining</b>	<b>3D-Mesh</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	37.07	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	297	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	Dry 25600 cycles/Wet 12800 cycles	25600/12800
<b>Outsole</b>	<b>ETPU/Rubber (NBR)</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	114	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.47	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.45	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.35	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.32	≥ 0.22
	Antistatic value	MegaOhm	42.6	0.1 - 1000
	ESD value	MegaOhm	20	0.1 - 100
	Heel energy absorption	J	33	≥ 20
<b>Toecap</b>	<b>Nano Carbon</b>			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	16.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	23.0	≥ 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.