

Medium

FREEDOM S3S LOW

FYTS3SL

Low Barefoot-like Walking Safety Shoe for Challenging Environments

FREEDOM S3S LOW is a low barefoot-style safety shoe with anatomical toe cap, Tiger Grip traction, ESD protection and rugged scuff cap.

Upper	TPU, Microfiber
Lining	Recycled Mesh
Footbed	SJ foam footbed
Midsole	Anti-Puncture Nonwoven
Outsole	ETPU/Rubber (NBR)
Toecap	Nano Carbon
Category	S3S / SR, SC, FO, HI, HRO, CI, ESD
Size range	EU 35-50 / UK 3.0-14.0 / US 3.0-15.0 JPN 21.5-33.0 / KOR 230-330
Sample weight	0.572 kg
Norms	EN ISO 20345:2022+A1:2024 ASTM F2413:2024



Barefoot-like walking

Anatomical toecap: barefoot-like walking for natural movement and reduced fatigue.



Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.




Heat resistant outsole (HRO)

The outsole resists high temperatures up to 300°C.



Tiger Grip Technology

Outsoles with Tiger Grip technology are renowned for their slip resistance, ability to withstand wear and tear and excellent traction on different surfaces, even wet and uneven ones. They are crafted with an exclusive rubber compound and engineered with specific patterns and grooves to enhance grip and stability.



Metal free

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



BLK

Industries:

Industry, Assembly, Automotive, Catering, Cleaning, Logistics, Construction

Environments:

Dry environment, Extreme slippery surfaces, Wet environment, Warm surfaces, Uneven surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	TPU, Microfiber			
	Upper: permeability to water vapor	mg/cm² /h		≥ 0.8
	Upper: water vapor coefficient	mg/cm²		≥ 15
Lining	Recycled Mesh			
	Lining: permeability to water vapor	mg/cm² /h		≥ 2
	Lining: water vapor coefficient	mg/cm²		≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles		25600/12800
Outsole	ETPU/Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm³		≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction		≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction		≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction		≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction		≥ 0.22
	Antistatic value	MegaOhm		0.1 - 1000
	ESD value	MegaOhm		0.1 - 100
	Heel energy absorption	J		≥ 20
Toecap	Nano Carbon			
	Impact resistance toecap (clearance after impact 100J)	mm		N/A
	Compression resistance toecap (clearance after compression 10kN)	mm		N/A
	Impact resistance toecap (clearance after impact 200J)	mm		≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm		≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.