



SAFETY JOGGER

INDUSTRIAL



Light

GOBI EH LOW SB

GOBIEH

EH-rated, low-cut safety shoe with premoulded footbed

Safety Jogger's GOBIEH is a low-cut safety shoe perfect for automotive, logistics, and construction sectors. It offers S1P and SR slip resistance, steel toe and midsole protection, and heel energy absorption.

Upper	Mesh, Suede Leather
Lining	Mesh
Footbed	SJ foam footbed
Category	SB / P, SRC, E, FO, EH
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.630 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011



BLK



Electrical hazard (EH)

Electrical hazard (EH) rated safety shoes have nonconductive outsoles. As a secondary source of protection they reduce the potential for electric shocks under dry conditions.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



Steel midsole

Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



Steel toe cap

Robust metal support to protect the feet of the wearer against falling or rolling objects.



S1P

You work in dry environments, no risk of water/liquid sprays, and you need protection for your toes, protection against perforation, and a good breathability? Then you need S1P safety footwear.

SAFETY JOGGER
WORKS

HEAD-TO-TOE PROTECTION



Proudly ranked in the top 1% by EcoVadis for sustainability.

ENGINEERED IN EUROPE

www.safetyjogger.com

Industries:
Automotive, Construction, Logistics, Industry

Environments:
Dry environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Mesh, Suede Leather			
	Upper: permeability to water vapor	mg/cm ² /h	2.2	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	20	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	48.7	≥ 2
	Lining: water vapor coefficient	mg/cm ²	389	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com