

Heavy

GORA S7S HIGH

GORAS7

High safety boot with breathable leather upper and Tiger Grip Technology

GORA S7S waterproof safety boots keeps your feet dry and delivers heat resistance, superior grip and lightweight comfort for tough industrial work.

Upper	Abrasion Resistant Leather
Lining	Membrane
Footbed	SJ foam footbed
Midsole	Anti-puncture Textile
Outsole	PU/Rubber (NBR)
Toecap	Composite
Category	S7S / SR, SC, LG, ESD, HI, CI, FO, HRO
Size range	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
Sample weight	0.920 kg
Norms	ASTM F2413:2018 EN ISO 20345:2022



BLK



Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.




Composite toecap

Metalfree and lightweight, no thermal or electrical conductivity



Heat resistant outsole (HRO)

The outsole resists high temperatures up to 300°C.



Oil & fuel resistant

The outsole is resistant against oil and fuel.



Puncture resistant lightweight

Metal free, super flexible and ultralight puncture resistant midsole. Covers 100% of the bottom area of the last, no thermal conductivity.



Scuff Cap (SC)

Separately tested material to cover the toe cap area to reduce abrasion of the upper material (e.g. during kneeling operations) and extend usability of the safety shoe.

Industries:

Mining, Construction, Oil & Gas, Industry

Environments:

Cold environment, Extreme slippery surfaces, Muddy environment, Uneven surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Abrasion Resistant Leather			
	Upper: permeability to water vapor	mg/cm²/h	3.3	# 0.8
	Upper: water vapor coefficient	mg/cm²	36	# 15
Lining	Membrane			
	Lining: permeability to water vapor	mg/cm²/h	6.3	# 2
	Lining: water vapor coefficient	mg/cm²	51	# 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	PU/Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm³	122	# 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.41	# 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.37	# 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.28	# 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.25	# 0.22
	Antistatic value	MegaOhm	54	0.1 - 1000
	ESD value	MegaOhm	58	0.1 - 100
	Heel energy absorption	J	28	# 20
Toecap	Composite			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	17	# 14
	Compression resistance toecap (clearance after compression 15kN)	mm	22	# 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com