



#####

JACKMAN S3

#####

JACKMAN#####SR##
#####

SJ####

S3 / SR, ####, ####, ######, ######, HRO
EU 35-48 / UK 3.0-13.0 / US 3.0-13.5
JPN 21.5-31.5 / KOR 230-315
0.720 kg
EN ISO 20345:2022+A1:2024
ASTM F2413:2024



#####




#####



#####



#####



#####



S3
S3#####
#####

#####:
####, ##, ####, #####, ####

#####:
####, #####, ####, ####

#####:
#####

####		####	##	EN ISO 20345
####	#####			
	#####	mg/cm ² /h	9.1	# 0.8
	#####	mg/cm ²	74.0	# 15
##	####			
	#####	mg/cm ² /h	63.7	# 2
	#####	mg/cm ²	510	# 20
#####	SJ#####			
	#####	####	25600/12800	25600/12800
#####	##			
	#####	mm ³	92	# 150
	##### - #####NaLS - #####	#####	0.43	# 0.31
	##### - #####NaLS - #####	#####	0.42	# 0.36
	SR ### - ##### - #####	#####	0.28	# 0.19
	SR##### - ##### - #####	#####	0.33	# 0.22
	#####	#####	20.5	0.1 - 100
	ESD#	#####	N/A	0.1 - 100
	#####	J	32.0	# 20
#####	##			
	#####100J#	mm	N/A	N/A
	#####10kN#####	mm	N/A	N/A
	#####200J#	mm	20.5	# 14
	#####15kN#	mm	23.5	# 14

#####:

#####Safety Jogger #####



**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com