SAFETY JOGGER
PROFESSIONAL

Light

JULIA OB

JULIA2

Professional and stylish work shoe

The JULIA are the ideal work shoes for people who need a professional and stylish look without sacrificing comfort and safety. These shoes have a slip-resistant outsole with extra cushioning and a water-resistant leather upper, so you can work with confidence and keep going all day long.

Upper	Synthetic Leather
Lining	Mesh, Synthetic Leather
Footbed	SJ foam footbed
Outsole	PU/Rubber
Category	OB / E, FO, SRC
Size range	EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 JPN 21.5-26.5 / KOR 230-270
Sample weight	0.235 kg
Norms	EN ISO 20347:2012

BLK

Oxygrip / SJ Grip
Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.

Breathable upper
Increased moisture and temperature management for extended wearer comfort.

Industries:
Catering, Uniform

Environments:
Dry environment

	Description	Measure unit	Result	EN ISO 20347
Upper	**Synthetic Leather**			
	Upper: permeability to water vapor	mg/cm²/h	3.6	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	31	≥ 15
Lining	**Mesh, Synthetic Leather**			
	Lining: permeability to water vapor	mg/cm²/h	33.03	≥ 2
	Lining: water vapor coefficient	mg/cm²	264	≥ 20
Footbed	**SJ foam footbed**			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	**PU/Rubber**			
	Outsole abrasion resistance (volume loss)	mm³	115	≤ 150
	Outsole slip resistance SRA: heel	friction	0.44	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.45	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.33	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.38	≥ 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	27	≥ 20

Sample size: 37

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.