



Light

JUNO 01 TLS

JUN001TLS

Fashionable Sneaker With TLS Closure

JUNO occupational lightweight sneakers with climate optimized comfort, heel energy absorption, antistatic grip and washable outsole.

| | |
|---------------|---|
| Upper | 3D-Mesh |
| Lining | Mesh |
| Footbed | SJ foam footbed |
| Outsole | Recycled Phylon/Rubber (NBR) |
| Category | O1 / SR, FO |
| Size range | EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315 |
| Sample weight | 0.260 kg |
| Norms | ASTM F2892:2018 EN ISO 20347:2022(Europe) |



BLU



DGR



BLK



WHT




TLS (Twist Lock System)

Safety Jogger's innovative TLS closure allows you to quickly tighten and loosen your safety footwear with one hand and under any conditions, even when you are wearing safety gloves. TLS ensures a fast, safe and easy precision fit that offers enhanced comfort and enables you to perform at your best.



Breathable upper

Increased moisture and temperature management for extended wearer comfort.



Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+SRB) standards.




SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



3D mesh

Three-dimensional produced distance mesh to provide increased moisture and temperature management.



Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

Industries:

Catering, Food & beverages, Medical, Uniform

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20347 |
|----------------|---|-----------------------|-------------|--------------|
| Upper | 3D-Mesh | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 25.3 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 204 | ≥ 15 |
| Lining | Mesh | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 21.1 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 169 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | Recycled Phylon/Rubber (NBR) | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 90 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.42 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.41 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.18 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.23 | ≥ 0.18 |
| | Antistatic value | MegaOhm | 30.5 | 0.1 - 1000 |
| | ESD value | MegaOhm | N/A | 0.1 - 100 |
| | Heel energy absorption | J | 30 | ≥ 20 |

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.