



# SAFETY JOGGER

PROFESSIONAL



Light

## JUNO 01 TLS

JUNO01TLS

**Fashionable Sneaker With TLS Closure**

JUNO occupational lightweight sneakers with climateoptimized comfort, heel energy absorption, antistatic grip and washable outsole.

Upper	3D-Mesh
Lining	Mesh
Footbed	SJ foam footbed
Outsole	Recycled Phylon/Rubber (NBR)
Category	O1 / SR, FO
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.260 kg
Norms	ASTM F2892:2018 EN ISO 20347:2022(Europe)



DGR



BLK



BLU



WHT




### TLS (Twist Lock System)

Safety Jogger's innovative TLS closure allows you to quickly tighten and loosen your safety footwear with one hand and under any conditions, even when you are wearing safety gloves. TLS ensures a fast, safe and easy precision fit that offers enhanced comfort and enables you to perform at your best.



### Breathable upper

Increased moisture and temperature management for extended wearer comfort.



### Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



### SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



### 3D mesh

Three-dimensional produced distance mesh to provide increased moisture and temperature management.



### Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

**SAFETY JOGGER**  
WORKS

**HEAD-TO-TOE PROTECTION**



Proudly ranked in the top 1% by EcoVadis for sustainability.

**ENGINEERED IN EUROPE**

[www.safetyjogger.com](https://www.safetyjogger.com)

Industries:

Catering, Food & beverages, Medical, Uniform

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	3D-Mesh			
	Upper: permeability to water vapor	mg/cm²/h	25.3	# 0.8
	Upper: water vapor coefficient	mg/cm²	204	# 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm²/h	21.1	# 2
	Lining: water vapor coefficient	mg/cm²	169	# 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	Recycled Phylon/Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm³	90	# 150
	Outsole slip resistance SRA: heel	friction	0.42	# 0.28
	Outsole slip resistance SRA: flat	friction	0.41	# 0.32
	Outsole slip resistance SRB: heel	friction	0.18	# 0.13
	Outsole slip resistance SRB: flat	friction	0.23	# 0.18
	Antistatic value	MegaOhm	30.5	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	30	# 20

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE  
PROTECTION



Proudly ranked in the  
top 1% by EcoVadis  
for sustainability.



www.safetyjogger.com