



JUNO O1 TLS

JUNOO1TLS

TLS#####

JUNO#Kassie#####
#####JUNO#####
#####30#####

| | |
|-------|--------------------------------------|
| #### | 3D#### |
| ## | #### |
| ##### | SJ##### |
| ##### | #####/### |
| ##### | O1 / SR, ##### |
| ##### | EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 |
| | JPN 21.5-31.5 / KOR 230-315 |
| ##### | 0.260 kg |
| ## | ASTM F2892:2018 |
| | EN ISO 20347:2022(Europe) |



BLK



DGR



BLU



WHT




TLS#####
Safety Jogger#####TLS#####
#####TLS#####

#####



#####



SJ#####
Oxytraction®#####
##SRC#SRA+ SRB#####



SRC###
#####1##
##SRC#####SRA#SRB#####
###



3D###

#####



#####

#####:

#####, #####, #####, #####

#####:

#####, #####

#####:

#####

| #### | | #### | ## | EN ISO 20347 |
|-------|----------------|-----------------------|-------------|--------------|
| #### | 3D-#### | | | |
| | ##### | mg/cm ² /h | 25.3 | # 0.8 |
| | ##### | mg/cm ² | 204 | # 15 |
| ## | #### | | | |
| | ##### | mg/cm ² /h | 21.1 | # 2 |
| | ##### | mg/cm ² | 169 | # 20 |
| ##### | SJ##### | | | |
| | ##### | #### | 25600/12800 | 25600/12800 |
| ##### | ##### | | | |
| | ##### | mm ³ | 90 | # 150 |
| | ##### SRA#### | #### | 0.42 | # 0.28 |
| | ##### SRA#### | #### | 0.41 | # 0.32 |
| | ##### SRB#### | #### | 0.18 | # 0.13 |
| | ##### SRB#### | #### | 0.23 | # 0.18 |
| | #### | #### | 30.5 | 0.1 - 1000 |
| | ESD# | #### | N/A | 0.1 - 100 |
| | ##### | J | 30 | # 20 |

#####:

#####Safety Jogger #####



**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com