

SAFETY JOGGER

PROFESSIONAL

Light

KASSIE 01

Breathable youthful work sneaker

Sporty design meets breathability. Kassie is both youthful and stylish combined with first-class wearer comfort and slip resistance, thanks to its lightweight design, climate-optimized high-tech materials, and ergonomically designed outsole. Kassie the ideal companion for the working day and beyond.

Upper	3D-Mesh
Lining	Mesh
Footbed	SJ foam footbed
Outsole	Phylon/Rubber (NBR)
Category	O1 / A, SRC
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.268 kg
Norms	ASTM F2892:2018 EN ISO 20347:2012



BLK



BLU



DGR



WHT



Breathable upper

Increased moisture and temperature management for extended wearer comfort.



Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



3D mesh

Three-dimensional produced distance mesh to provide increased moisture and temperature management.



Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



SJ Foam

Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.

Industries:

Catering, Cleaning, Food & beverages, Medical, Uniform

Environments:

Dry environment, Extreme slippery surfaces, Uneven surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	3D-Mesh			
	Upper: permeability to water vapor	mg/cm ² /h	25.3	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	204	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	21.1	≥ 2
	Lining: water vapor coefficient	mg/cm ²	169	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	Phylon/Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm ³	74.2	≤ 150
	Outsole slip resistance SRA: heel	friction	0.41	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.39	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.17	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	147	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	24	≥ 20

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.