



# SAFETY JOGGER

## PROFESSIONAL



Light

## LAUREN

### Light and airy shoe with a adjustable strap

The LAUREN clogs offer exceptional comfort and moisture management. Equipped with an adjustable strap, vegan-friendly and suitable for various industries, these shoes combine performance and affordability.

Upper	Mesh, Synthetic
Lining	Mesh
Footbed	Oxy Basic
Outsole	EVA
Size range	EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 JPN 21.5-26.5 / KOR 230-270
Sample weight	0.135 kg



WHT



BLK



#### Breathable upper

Increased moisture and temperature management for extended wearer comfort.



#### Coolmax® lining

Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



#### Vegan

Uses or contains no animal products.

**SAFETY JOGGER**  
WORKS

**HEAD-TO-TOE PROTECTION**



Proudly ranked in the top 1% by EcoVadis for sustainability.

**ENGINEERED IN EUROPE**

[www.safetyjogger.com](http://www.safetyjogger.com)

**Industries:**  
Catering, Cleaning, Food & beverages, Medical

**Environments:**  
Dry environment

**Maintenance instructions:**  
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	
Upper	<b>Mesh, Synthetic</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	N/A	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	N/A	≥ 15
Lining	<b>Mesh</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	N/A	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	N/A	≥ 20
Footbed	<b>Oxy Basic</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	<b>EVA</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	N/A	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	N/A	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	N/A	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	N/A	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	N/A	≥ 0.22
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	N/A	≥ 20

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE  
PROTECTION



Proudly ranked in the  
top 1% by EcoVadis  
for sustainability.



www.safetyjogger.com