



#####

LIGHTSTAR S1PS

LIGHTSTAR

#####

LIGHTSTAR S1PS#####

#####, #####

SJ#####

EVA/##

S1 PS / SR, SC, ESD, ####, #####, HRO
EU 35-48 / UK 3.0-13.0 / US 3.0-13.5
JPN 21.5-31.5 / KOR 230-315
0.448 kg
ASTM F2413:2018
EN ISO 20345:2022+A1:2024



(SR)
SRA+SRB=SRC#####
SR#####
#####



#####

#####100#####



BLK



#####



BLK

#####

#####



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

#####:
##, #####, ##, #####

#####:
##, #####

#####:
#####

	####	####	##	EN ISO 20345
####	#####, ####			
	#####	mg/cm ² /h	33.2	# 0.8
	#####	mg/cm ²	265.5	# 15
##	####			
	#####	mg/cm ² /h	86.31	# 2
	#####	mg/cm ²	691	# 20
####	SJ#####			
	#####	####	Dry 25600 cycles/Wet 12800 cycles	25600/12800
#####	EVA/##			
	#####	mm ³	102.2	# 150
	##### - #####NaLS - #####	####	0.49	# 0.31
	##### - #####NaLS - #####	####	0.46	# 0.36
	SR #### - ##### - #####	####	0.36	# 0.19
	SR##### - ##### - #####	####	0.34	# 0.22
	####	####	68.0	0.1 - 1000
	ESD#	####	21	0.1 - 100
	#####	J	33	# 20
#####	####			
	#####100J#	mm	N/A	N/A
	#####10kN#####	mm	N/A	N/A
	#####200J#	mm	15.5	# 14
	#####15kN#	mm	22.0	# 14

#####:

#####Safety Jogger #####



**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com