



Light

LOGAN O1

LOGANO1

Lightweight and breathable slip-on shoe with elastic laces

The LOGAN O1 occupational shoes offer ultimate comfort thanks to their lightweight, breathable design. They feature a stretchable upper and elastic laces for an unbeatable fit. Perfect for the logistics, medical, and catering industries.

Upper	TPU, 3D-Mesh
Lining	Textile
Footbed	SJ foam footbed
Outsole	EVA/Rubber (NBR)
Category	O1 / SR, ESD, FO, HRO
Size range	EU 35-48
Sample weight	0.315 kg
Norms	ASTM F2892:2018 EN ISO 20347:2022+A1:2024



WHT



BLK



Slip resistance (SR)

Replaces the previously used term of SRA+SRB=SRC. SR means the slip test has been executed on tiles contaminated with soap and with oil.



Stretchable upper

Super elastic and stretchable textile for improved comfort and fit.




Breathable upper

Increased moisture and temperature management for extended wearer comfort.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Metal free

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



SJ Foam

Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.

Industries:

Logistics, Medical, Catering

Environments:

Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	TPU, 3D-Mesh			
	Upper: permeability to water vapor	mg/cm ² /h	48.1	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	384.8	≥ 15
Lining	Textile			
	Lining: permeability to water vapor	mg/cm ² /h	48.1	≥ 2
	Lining: water vapor coefficient	mg/cm ²	384.8	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	Dry 25600 cycles/Wet 12800 cycles	25600/12800
Outsole	EVA/Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm ³	118.6	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.56	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.58	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.20	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.28	≥ 0.22
	Antistatic value	MegaOhm	33.6	0.1 - 1000
	ESD value	MegaOhm	19	0.1 - 100
	Heel energy absorption	J	34	≥ 20

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.