



###

MAGO S3 MID

MAGOS3MID

#####

MAGO S3 #####

####	#####
##	####
####	SJ#####
#####	#####
#####	##
#####	#####
#####	S3 / SRC, HRO
#####	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5
#####	JPN 21.5-31.5 / KOR 230-315
#####	0.707 kg
##	ASTM F2413:2018
	EN ISO 20345:2011




#####100 KiloOhm##1 GigaOhm
#####



#####



#####



#####



#####



#####



BLK

#####:

####, ##, ####, #####, ##

#####:

####, ####, #####, ####

#####:

#####

	####	####	##	EN ISO 20345
####	#####			
	#####	mg/cm²/h	4.47	# 0.8
	#####	mg/cm²	38	# 15
##	####			
	#####	mg/cm²/h	56.3	# 2
	#####	mg/cm²	451	# 20
#####	SJ#####			
	#####	####	25600/12800	25600/12800
#####	##			
	#####	mm³	123	# 150
	##### SRA###	####	0.30	# 0.28
	##### SRA###	####	0.34	# 0.32
	##### SRB###	####	0.20	# 0.13
	##### SRB###	####	0.26	# 0.18
	####	####	Dry:16.9, Wet:5.6	0.1 - 1000
	ESD#	####	Not applicable	0.1 - 100
	#####	J	30	# 20
#####	#####			
	#####100J#	mm	Not applicable	N/A
	#####10kN#####	mm	Not applicable	N/A
	#####200J#	mm	20.5	# 14
	#####15kN#	mm	24.0	# 14

#####:

#####Safety Jogger #####



**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com