

MAMBA 06 MID

MAMBAMID

mid-cut occupational shoe with waterproof membrane and heat-resistant outsole

MAMBA 06 MID offers superior foot protection with its waterproof membrane, rubber outsole and cold insulation.

	-
Upper	TPU, Mesh, Textile
Lining	Membrane
Footbed	SJ foam footbed
Outsole	Phylon/Rubber (NBR)
Category	06 / SR, SC, ESD, CI, HRO
Size range	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
Sample weight	0.476 kg
Norms	EN ISO 20347:2022+A1:2024 ASTM F2892:2024







































Industries:

Tactical, Uniform

Environments:

Extreme slippery surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	TPU, Mesh, Textile			
	Upper: permeability to water vapor	mg/ _{Cm²} /h	3.9	≥ 0.8
	Upper: water vapor coefficient	$mg/_{CM^2}$	32.3	≥ 15
Lining	Membrane			
	Lining: permeability to water vapor	$mg/_{Cm^2}/h$	4.90	≥2
	Lining: water vapor coefficient	$mg/_{\mathrm{Cm}^2}$	41	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	Dry 25600 cycles/Wet 12800 cycles	25600/12800
Outsole	Phylon/Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm ³	59	≤150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.46	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.47	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.28	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.25	≥ 0.22
	Antistatic value	Mega0hm	25.0	0.1 - 1000
	ESD value	Mega0hm	38	0.1 - 100
	Heel energy absorption	J	37	≥ 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.





Proudly ranked in the top 1% by EcoVadis for sustainability.

