

## Medium

## MODULO LEA S3S LOW T

MDLCHS3SLT

**Tiger Grip ### ## ## ## ## ##, ### ## ## ## ## ##**

```
### S3S #####
#####. Tiger Grip ##
#####
#####. #####.
```


|       |                                        |
|-------|----------------------------------------|
| ## ## | #### ## ##, ### ## ##                  |
| ## ## | 3D ##                                  |
| ##    | SJ # ##                                |
| ##    | ## ## ##                               |
| ## #  | ##, BASF PU                            |
| Top   | ####                                   |
| ####  | S3S / SR, SC, LG, ESD, ##, CI, FO, HRO |
| ## ## | EU 35-50                               |
| ## ## | 0.620 kg                               |
| ####  | EN ISO 20345:2022+A1:2024              |
|       | ASTM F2413:2024                        |



```
### ## ##
## ### ### ### ## # ## ##### ##
## ##### #####.
```



```
Tiger Grip-##
Tiger Grip ### ### ##### ##
###, ### ## ###, ### ##, ### ##
### ## ##### ## ##### #####. #
##### ## ## ##### ##### ## ##
## ## ##### ##### #####.
```



```
## ##
### ## ##### ## #####
#####. ## ## ##### ## # #####
## ##### ## #####.
```



**SJ FOAM**  
#### ### ### ## #### #####  
### ## #, ### # ### ## ## ##  
#####. ### # ## #.



### ###  
### ## 300°C# ### ## # ####.



#### # #####  
#### #### #### #####.

## ##:  
####, ##, ##, ##, ##, ##

## ##:  
### ##, ## ##### ##, ### ##, ### ## ##, ## ##

## ## ##:  
### ### ##### ##### ### ##### ### ##### ## #####. ### ##### ## ##### ### ##.

|       | ##                                    | ## ##    | ##                                | EN ISO 20345 |
|-------|---------------------------------------|----------|-----------------------------------|--------------|
| ## ## | ##### ## ##, ### ## ##                |          |                                   |              |
|       | ##: ### ##                            | mg/cm²/h | 7.8                               | # 0.8        |
|       | ##: ### ##                            | mg/cm²   | 68                                | # 15         |
| ## ## | 3D ##                                 |          |                                   |              |
|       | ##: ### ##                            | mg/cm²/h | 42.7                              | # 2          |
|       | ##: ### ##                            | mg/cm²   | 342.3                             | # 20         |
| ##    | SJ # ##                               |          |                                   |              |
|       | ###: ####(##/##)(###)                 | ##       | Dry 25600 cycles/Wet 12800 cycles | 25600/12800  |
| ## #  | ##, BASF PU                           |          |                                   |              |
|       | ### #####(## ##)                      | mm³      | 117                               | # 150        |
|       | ## ### ## - ### + NaLS - ## ### ##### | ##       | 0.44                              | # 0.31       |
|       | ## ### ## - ### + NaLS - ## ## ##     | ##       | 0.42                              | # 0.36       |
|       | SR ### ## - ### + ##### - ##### ## ## | ##       | 0.29                              | # 0.19       |
|       | SR ### ## - ### + ##### - ## ## ##    | ##       | 0.32                              | # 0.22       |
|       | ### ## #                              | ###      | 32.1                              | 0.1 - 1000   |
|       | ESD #                                 | ###      | 65                                | 0.1 - 100    |
|       | #### ## ##                            | J        | 37                                | # 20         |
| Top   | ####                                  |          |                                   |              |
|       | #### ## ##(## # ## 100J)              | mm       | N/A                               | N/A          |
|       | #### ## ##(## # ## ## 10kN)           | mm       | N/A                               | N/A          |
|       | #### ## ##(## # ## 200J)              | mm       | 17.0                              | # 14         |
|       | ### ## ## ##(## # ## ## 15kN)         | mm       | 21.5                              | # 14         |

### ##:  
##### ## ##### ##### ##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



HEAD-TO-TOE  
PROTECTION



Proudly ranked in the  
top 1% by EcoVadis  
for sustainability.



www.safetyjogger.com