

Medium

MODULO ARMOR S3S MID

MDLOAMRS3M

Super Breathable S3S Mid Safety Shoes

MODULO ARMOR S3S MID safety shoes features a breathable upper, ESD, slip resistance and vegan, metalfree comfort. Built tough for demanding environments.

Upper	Abrasion resistant fabric, Abrasion Resistant Synthetic
Lining	3D-Mesh
Footbed	SJ foam footbed
Midsole	Anti-puncture Textile
Outsole	BASF PU/BASF PU
Toecap	Nano Carbon
Category	S3S / SR, SC, ESD, CI, FO
Size range	EU 35-50
Sample weight	0.595 kg
Norms	EN ISO 20345:2022+A1:2024 ASTM F2413:2024



BLK




Breathable upper

Increased moisture and temperature management for extended wearer comfort.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Metal free

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



Oil & fuel resistant

The outsole is resistant against oil and fuel.



Scuff Cap (SC)

Separately tested material to cover the toe cap area to reduce abrasion of the upper material (e.g. during kneeling operations) and extend usability of the safety shoe.



Vegan

Uses or contains no animal products.

Industries:

Assembly, Automotive, Catering, Cleaning, Construction, Industry, Logistics

Environments:

Dry environment, Extreme slippery surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Abrasion resistant fabric, Abrasion Resistant Synthetic			
	Upper: permeability to water vapor	mg/cm²/h	3.26	# 0.8
	Upper: water vapor coefficient	mg/cm²	27	# 15
Lining	3D-Mesh			
	Lining: permeability to water vapor	mg/cm²/h	60.62	# 2
	Lining: water vapor coefficient	mg/cm²	485	# 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	Dry 25600 cycles/Wet 12800 cycles	25600/12800
Outsole	BASF PU/BASF PU			
	Outsole abrasion resistance (volume loss)	mm³	86	# 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.34	# 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.39	# 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.32	# 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.40	# 0.22
	Antistatic value	MegaOhm	23.6	0.1 - 1000
	ESD value	MegaOhm	40	0.1 - 100
	Heel energy absorption	J	31	# 20
Toecap	Nano Carbon			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	15.5	# 14
	Compression resistance toecap (clearance after compression 15kN)	mm	21.0	# 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com