

Medium

MODULO ARMOR S3S MID

MDLOAMRS3M

2## ## PU ##### ##### ##### ##### ## ## ## ## ##.

MODULO ARMOR S3S ## ## ## ### ### #####. ##### ##
MAX TEK ### ### ## ##, ### ## ## ##### ## ## ##
####.


## ##	#### ##, ### ## ##
## ##	3D ##
##	SJ # ##
##	## ## ##
## #	### PU/### PU
Top	####
####	S3S / SR, SC, ESD, CI, FO
## ##	EU 35-50
## ##	0.595 kg
###	EN ISO 20345:2022+A1:2024
	ASTM F2413:2024




```
### ##
### ## # ## ## ##### ## ## ##
# #####.
```



```
### ##
ESD# ## ### ##### # ## ### #####
### ##### ##### ## ## ### #####. ##
### 100##### 100### #####.
```



```
## ##
### ## ##### ## #####
#####. ## ## ##### ## # #####
## ##### ## #####.
```



#####.



```
### #(SC)
### ## # # ## ### ### ####
##### ## ## ### ## ## ##
##### ## ### #####.
```



```
##
#### ##### ##### #####.
```

##:
####, ###, ####, ##, ##, ##, ##

##:
##, ## ##### ##, ##

##:
#####. ### ##### ## ##### ### ##.

	##	## ##	##	EN ISO 20345
## ##	#### ##, ### ## ##			
	##: ### ##	mg/cm²/h	3.26	# 0.8
	##: ### ##	mg/cm²	27	# 15
## ##	3D ##			
	##: ### ##	mg/cm²/h	60.62	# 2
	##: ### ##	mg/cm²	485	# 20
##	SJ # ##			
	###: ####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
## #	### PU/### PU			
	### #####(## ##)	mm³	86	# 150
	## ### ## - ### + NaLS - ## ### #####	##	0.34	# 0.31
	## ### ## - ### + NaLS - ## ## ##	##	0.39	# 0.36
	SR ### ## - ### + ##### - ##### ## ##	##	0.32	# 0.19
	SR ### ## - ### + ##### - ## ## ##	##	0.40	# 0.22
	### ## #	###	23.6	0.1 - 1000
	ESD #	###	40	0.1 - 100
	#### ## ##	J	31	# 20
Top	####			
	#### ## ##(## # ## 100J)	mm	N/A	N/A
	#### ## ##(## # ## ## 10kN)	mm	N/A	N/A
	#### ## ##(## # ## 200J)	mm	15.5	# 14
	### ## ## ##(## # ## ## 15kN)	mm	21.0	# 14

##:
##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com