



## MODULO ARMOR S3S MID

MDLOAMRS3M

##### PU 2 #####  
##### MODULO ARMOR S3S ##### MAX TEK

##### MODULO ARMOR S3S / #####, #, ESD, #, #, #####  
##### SJ #####  
##### BASF PU/BASF PU

##### 3 #####  
##### SJ #####  
##### 0.595 kg  
##### EN ISO 20345:2022+A1:2024  
##### ASTM F2413:2024




##### (ESD)



##### (ESD)

ESD ##### 100 ##### 100 ##### #####  
##### 100 ##### 100 ##### #####  
##### #####



##### (SC)



##### (SC)



##### (Vegan)



##### (Vegan)

PLATINUM  
Top 1%



Proudly ranked in the  
top 1% by EcoVadis  
for sustainability.

#####:

#####, #####, #####, #####, #####, #####, #####, #####, #####

#####:

#####, #####, #####, #####

#####:

##### ##### ##### ##### ##### ##### ##### ##### ##### #####

				EN ISO 20345
#####	#####, #####			
#####:	#####	##./##./##	3.26	# 0.8
#####:	#####	##./##	27	# 15
#####	##### 3 #####			
#####:	#####	##./##./##	60.62	# 2
#####:	#####	##./##	485	# 20
#####	SJ #####			
#####:	##### (#####) (###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
<b>BASF PU/BASF PU</b>				
#####	##### (#####)	##	86	# 150
#####	##### - ##### + NaLS - #####	#####	0.34	# 0.31
#####	##### - ##### + NaLS - #####	#####	0.39	# 0.36
SR Slip Resistance - Ceramic + Glycerin - #####	#####	#####	0.32	# 0.19
##### SR - ##### + ##### - #####	#####	#####	0.40	# 0.22
#####	#####	#####	23.6	0.1 - 1000
### ESD	#####	#####	40	0.1 - 100
#####	#####	##	31	# 20
#####	#####			
#####	##### (##### 100J)	##	N/A	N/A
#####	##### (##### 10kN)	##	N/A	N/A
#####	##### (##### 200J)	##	15.5	# 14
#####	##### (##### 15kN)	##	21.0	# 14

#####.

##### Safety Jogger #####



**HEAD-TO-TOE  
PROTECTION**



Proudly ranked in the  
top 1% by EcoVadis  
for sustainability.

ENGINEERED  
IN EUROPE

[www.safetyjogger.com](http://www.safetyjogger.com)