



Medium

MODULO DELTA 06 HIGH

MDLODLTHIG

Waterproof High Occupational Shoes

MODULO DELTA 06 HIGH waterproof leather shoes give workers secure grip, slip & heat resistance, and lasting protection indoors and outdoors.


Upper	Abrasion Resistant Synthetic, Milled Full-Grain Leather
Lining	Recycled Mesh, Membrane
Footbed	SJ foam footbed
Outsole	BASF PU/Rubber (NBR)
Category	06 / SR, SC, LG, ESD, HI, CI, FO, HRO
Size range	EU 37-48 / UK 4.0-13.0 / US 4.5-13.5 JPN 23-31.5 / KOR 240-315
Sample weight	0.650 kg
Norms	EN ISO 20347:2022+A1:2024 ASTM F2892:2024




BLK



Breathable leather upper
Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.




Waterproof (WR)
Waterproof footwear prevents liquids to enter into the shoe.



Electrostatic Discharge (ESD)
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Heat resistant outsole (HRO)
The outsole resists high temperatures up to 300°C.



Heel energy absorption
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



Oil & fuel resistant
The outsole is resistant against oil and fuel.

Industries:

Tactical, Uniform

Environments:

Extreme slippery surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Abrasion Resistant Synthetic, Milled Full-Grain Leather			
	Upper: permeability to water vapor	mg/cm ² /h	2.71	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	26	≥ 15
Lining	Recycled Mesh, Membrane			
	Lining: permeability to water vapor	mg/cm ² /h	6.36	≥ 2
	Lining: water vapor coefficient	mg/cm ²	51	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	Dry 25600 cycles/Wet 12800 cycles	25600/12800
Outsole	BASF PU/Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm ³	117	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.44	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.42	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.29	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.32	≥ 0.22
	Antistatic value	MegaOhm	28.4	0.1 - 1000
	ESD value	MegaOhm	33	0.1 - 100
	Heel energy absorption	J	35	≥ 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.