



###

MODULO LE S3S LOW TG

MDLOLEAS3L

#####

##Tiger Grip #####

MODULO LE S3S LOW #####

#####Tiger Grip #####

####	#####, #####
##	3D-####
####	SJ#####
#####	#####
#####	##, BASF PU
#####	#####
####	S3S / SR, SC, ###, ESD, ####, #####, #####, HRO
####	EU 35-48
#####	0.610 kg
##	EN ISO 20345:2022+A1:2024
	ASTM F2413:2024



BLK



#####




#####HRO#
#####300#####




#####LG#


#####



#####



#####



#####

####:
##, ####, ##, ####, ####, ####, ####

#####:
#####, ####, ####

#####:
#####

	####	####	##	EN ISO 20345
####	#####, #####			
	#####	mg/cm²/h	2.71	# 0.8
	#####	mg/cm²	26	# 15
##	3D-####			
	#####	mg/cm²/h	42.7	# 2
	#####	mg/cm²	342.3	# 20
####	SJ#####			
	#####	####	Dry 25600 cycles/Wet 12800 cycles	25600/12800
#####	##, BASF PU			
	#####	mm³	117	# 150
	##### - #####NaLS - #####	#####	0.44	# 0.31
	##### - #####NaLS - #####	#####	0.42	# 0.36
	SR ### - ##### - #####	#####	0.29	# 0.19
	SR##### - ##### - #####	#####	0.32	# 0.22
	####	#####	32.1	0.1 - 1000
	ESD#	#####	63	0.1 - 100
	#####	J	37	# 20
#####	#####			
	#####100J#	mm	N/A	N/A
	#####10kN#####	mm	N/A	N/A
	#####200J#	mm	17.0	# 14
	#####15kN#	mm	21.5	# 14

#####.
#####Safety Jogger #####



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com