



Heavy

MODULO LE S3S LOW TG

MDLOLEAS3L

Tiger Grip ### ### ## ### ## ## ## ## ##
#####.

##, ### ## ##, ### ## ## ##, ## ### ## Tiger Grip #####
MODULO LE S3S LOW ## #####.

## ##	# ### ##, ### ## ##
## ##	3D ##
##	SJ # ##
##	## ## ##
## #	##, BASF PU
Top	####
####	S3S / SR, SC, LG, ESD, ##, CI, FO, HRO
## ##	EU 35-48
## ##	0.610 kg
###	EN ISO 20345:2022+A1:2024
	ASTM F2413:2024



#####.

300°C# ### ## ## ## ##.

##(LG)

##.

##, ### # ##, ##
##, ##, ## # ## ## ## ##

#####.

##.

#####. ## ## ## ## ## ## ## ## ##
##.



BLK

##:
####, ##, ##, ## # ##, ####, ##, ##

##:
##, ### ##, ##

##:
#####. ### ##### ## ##### ### ##.

	##	## ##	##	EN ISO 20345
## ##	# ### ##, ### ## ##			
	##: ### ##	mg/cm²/h	2.71	# 0.8
	##: ### ##	mg/cm²	26	# 15
## ##	3D ##			
	##: ### ##	mg/cm²/h	42.7	# 2
	##: ### ##	mg/cm²	342.3	# 20
##	SJ # ##			
	###: ####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
## #	##, BASF PU			
	### #####(## ##)	mm³	117	# 150
	## ### ## - ### + NaLS - ## ### #####	##	0.44	# 0.31
	## ### ## - ### + NaLS - ## ## ##	##	0.42	# 0.36
	SR ### ## - ### + ##### - ##### ## ##	##	0.29	# 0.19
	SR ### ## - ### + ##### - ## ## ##	##	0.32	# 0.22
	### ## #	###	32.1	0.1 - 1000
	ESD #	###	63	0.1 - 100
	#### ## ##	J	37	# 20
Top	####			
	#### ## ##(## # ## 100J)	mm	N/A	N/A
	#### ## ##(## # ## ## 10kN)	mm	N/A	N/A
	#### ## ##(## # ## 200J)	mm	17.0	# 14
	### ## ## ##(## # ## ## 15kN)	mm	21.5	# 14

##:
##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com