



#####

MODULO LE S3S MID TG

MDLOLEAS3M

Tiger Grip

Tiger Grip ##### MODULO LE S3S MID #####

SRC ##### #####

#####	##### #####
#####	##### 3 #####
#####	SJ ##### #####
#####	##### #####
#####	###, BASF PU
#####	##### #####
#####	S3S / ###.###, ##, ####, ESD, #####, ##.##, ####, ##
#####	EU 35-50 / UK 3.0-14.0 / US 3.0-15.0 JPN 21.5-33.0 / KOR 230-330
#####	0.666 kg
#####	EN ISO 20345:2022+A1:2024
#####	ASTM F2413:2024



BLK



(HRO) 300 °C



#####



Tiger Grip
Tiger Grip

#####

#####:

#####:

████████████████████, █████████████████████, █████████████████████, █████████████████████

#####:

#####

#####	#####	#####	EN ISO 20345	
#####	#####, #####			
	###. ####	##./##./##	2.71	# 0.8
	###. ####	##./##	26	# 15
####	#### 3 ####			
	###. ####	##./##./##	42.7	# 2
	###. ####	##./##	342.3	# 20
#####	SJ #####			
	###. ##### (###/###) (###)	###	Dry 25600 cycles/Wet 12800 cycles	25600/12800

#####, BASF PU

##### (#####)	##	117	# 150
##### - ##### + NaLS - #####	#####	0.44	# 0.31
##### - ##### + NaLS - #####	#####	0.42	# 0.36
SR Slip Resistance - Ceramic + Glycerin - #####	#####	0.29	# 0.19
##### SR - ##### + ##### - #####	#####	0.32	# 0.22
#####	#####	32.1	0.1 - 1000
### ESD	#####	63	0.1 - 100
#####	##	37	# 20

```
#####
##### (##### 100J) ## N/A N/A
##### (##### 10kN) ## N/A N/A
##### (##### 200J) ## 17.0 # 14
##### (##### 15kN) ## 21.5 # 14
```

####:

Safety Jogger

