



## MODULO PURE S3S M TG

MDLPRS3MTG

Tiger Grip #####

##### Tiger Grip MODULO  
PURE#####


##### ####  
## 3D-###  
#### SJ#####  
#### #####  
#### ##, BASF PU  
#### #####  
#### S3S / SR, ESD, #####, #####, #####, HRO  
#### EU 35-50  
#### 0.612 kg  
## EN ISO 20345:2022+A1:2024  
ASTM F2413:2024



###  
#####  
##### HACCP###



Tiger Grip #####  
Tiger Grip #####  
#####  
#####  
#####



#####  
#####  
#####  
#####



##### HRO#  
##### 300#####



#####  
#####



HACCP  
HACCP#####  
#####  
##### HACCP###  
#####

#####:

##, #####, #####, #####, ##, #####, #####

#####:

#####, #####, #####, ##, ##

#####:

#####

	####	####	##	EN ISO 20345
####	###			
	#####	mg/cm <sup>2</sup> /h	1.80	# 0.8
	#####	mg/cm <sup>2</sup>	17	# 15
##	<b>3D-###</b>			
	#####	mg/cm <sup>2</sup> /h	18.2	# 2
	#####	mg/cm <sup>2</sup>	146.8	# 20
####	<b>SJ#####</b>			
	#####	####	Dry 25600 cycles/Wet 12800 cycles	25600/12800
#####	<b>##, BASF PU</b>			
	#####	mm <sup>3</sup>	124	# 150
	##### - #####NaLS - #####	####	0.38	# 0.31
	##### - #####NaLS - #####	####	0.45	# 0.36
	SR ### - ##### - #####	####	0.23	# 0.19
	SR##### - ##### - #####	####	0.26	# 0.22
	#####	####	57.1	0.1 - 1000
	ESD#	####	69	0.1 - 100
	#####	J	32	# 20
#####	<b>#####</b>			
	#####100J#	mm	N/A	N/A
	#####10kN#####	mm	N/A	N/A
	#####200J#	mm	17.0	# 14
	#####15kN#	mm	23.0	# 14

#####:

#####Safety Jogger #####



**HEAD-TO-TOE  
PROTECTION**



Proudly ranked in the  
top 1% by EcoVadis  
for sustainability.

ENGINEERED  
IN EUROPE

[www.safetyjogger.com](http://www.safetyjogger.com)