

## Medium

# MODULO PURE S3S M TG

MDLPRS3MTG

**Tiger Grip ### ### ### #### #### ## ## ###, #### ## ####  
#####.**

```
##, ## # ## ### ##### ## #####. Tiger Grip ### ## ## #### ## ##
#### ## ## #### ##### ##### #####. ### ## ## #### ## ## ####
##### #####. ## ## # ##.
```

|       |                                |
|-------|--------------------------------|
| ## ## | Lorica                         |
| ## ## | 3D ##                          |
| ##    | SJ # ##                        |
| ##    | ## ## ##                       |
| ## #  | ##, BASF PU                    |
| Top   | ####                           |
| ####  | S3S / SR, ESD, ##, CI, FO, HRO |
| ## ## | EU 35-50                       |
| ## ## | 0.612 kg                       |
| ####  | EN ISO 20345:2022+A1:2024      |
|       | ASTM F2413:2024                |




## Lorica

#####  
#####. #, ##, ### #####  
HACCP ## #####.



**Tiger Grip-##**

Tiger Grip ### ## ##### ##  
###, ## ## ##, ## ##, ## ##  
### ## ##### ## ##### ##. #  
#### ## ## ##### ##### ## ##  
## ## ##### #####.




## ##

####  
#####  
#####. ## ##  
## #####.



### ##

### ## 300°C# ### ## # ####.



#### # #####

#### #### #### ####.



## HACCP

HACCP# ### ##### ### ##  
# ## ### ## ## ##### ## ##  
#####. ## ### ## ### ## HACCP  
## ### ## ### ## #####.

## ##:  
####, ####, ##, ## # ##, ##, ##, ##  
  
## ##:  
### ##, ## ##### ##, ### ## ##, ### ##, ## ##  
  
## ## ##:  
### ### ##### ##### ## ##### ## ##### ## #####. ### ##### ## ##### ## ##.

|       | ##                                 | ## ##    | ##                                | EN ISO 20345 |
|-------|------------------------------------|----------|-----------------------------------|--------------|
| ## ## | Lorica                             |          |                                   |              |
|       | ##: ### ##                         | mg/cm²/h | 1.80                              | # 0.8        |
|       | ##: ### ##                         | mg/cm²   | 17                                | # 15         |
| ## ## | 3D ##                              |          |                                   |              |
|       | ##: ### ##                         | mg/cm²/h | 18.2                              | # 2          |
|       | ##: ### ##                         | mg/cm²   | 146.8                             | # 20         |
| ##    | SJ # ##                            |          |                                   |              |
|       | ###: ####(##/##)(###)              | ##       | Dry 25600 cycles/Wet 12800 cycles | 25600/12800  |
| ## #  | ##, BASF PU                        |          |                                   |              |
|       | ### #####(## ##)                   | mm³      | 124                               | # 150        |
|       | ## ### ## - ### + NaLS - ## ## ##  | ##       | 0.38                              | # 0.31       |
|       | ## ### ## - ### + NaLS - ## ## ##  | ##       | 0.45                              | # 0.36       |
|       | SR ### ## - ### + ##### - ##### ## | ##       | 0.23                              | # 0.19       |
|       | SR ### ## - ### + ##### - ## ## ## | ##       | 0.26                              | # 0.22       |
|       | ### ## #                           | ###      | 57.1                              | 0.1 - 1000   |
|       | ESD #                              | ###      | 69                                | 0.1 - 100    |
|       | #### ## ##                         | J        | 32                                | # 20         |
| Top   | ####                               |          |                                   |              |
|       | #### ## ##(## # ## 100J)           | mm       | N/A                               | N/A          |
|       | #### ## ##(## # ## ## 10kN)        | mm       | N/A                               | N/A          |
|       | #### ## ##(## # ## 200J)           | mm       | 17.0                              | # 14         |
|       | ### ## ## ##(## # ## ## 15kN)      | mm       | 23.0                              | # 14         |

### ##:  
##### ## ##### ##### ##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



HEAD-TO-TOE  
PROTECTION



Proudly ranked in the  
top 1% by EcoVadis  
for sustainability.



www.safetyjogger.com