



SAFETY JOGGER

PROFESSIONAL



Heavy

MICKEY SONIC OB

MICSONIC

Light Hospital Clog with Mickey-Print

MICKEY SONIC OB clogs combine certified protection with iconic Mickey style, waterproof hygienic design, slip resistance, ESD safety and allday comfort.

| | |
|---------------|-------------------------------------------------------------------|
| Upper | Expanded EVA |
| Lining | N/A |
| Footbed | N/A |
| Outsole | EVA |
| Category | OB / ESD, A, SRC, E |
| Size range | EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310 |
| Sample weight | 0.150 kg |
| Norms | ASTM F2892:2018 EN ISO 20347:2012 |



WHT



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Washable 30°C

These shoes can be washed in a washing machine at 30°C.



Chemically & UV sterilizeable

This shoe is chemically and UV sterilizeable.



Hygienic waterproof solution

This shoe is made with materials that are waterproof, antibacterial and extremely light & flexible. This makes it a safe, hygienic and comfortable solution for applications in wet environments, such as cleaning or escorting patients into the shower.

SAFETY JOGGER
WORKS

HEAD-TO-TOE PROTECTION



Proudly ranked in the top 1% by EcoVadis for sustainability.

ENGINEERED IN EUROPE

www.safetyjogger.com

Industries:
Cleaning, Medical

Environments:
Wet environment, Dry environment, Uneven surfaces

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20347 |
|---------|-------------------------------------------------|-----------------------|-------------|--------------|
| Upper | Expanded EVA | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | N/A | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | N/A | ≥ 15 |
| Lining | N/A | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | N/A | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | N/A | ≥ 20 |
| Footbed | N/A | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | EVA | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 152 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.36 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.34 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.17 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.20 | ≥ 0.18 |
| | Antistatic value | MegaOhm | 0.69 | 0.1 - 1000 |
| | ESD value | MegaOhm | 0.07 | 0.1 - 100 |
| | Heel energy absorption | J | 47 | ≥ 20 |

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com