



#####

MILOS S1P LOW S1 PS

MILOSS1PL

#####


###MILOS S1P#####
#####ESD#####
###MILOS S1P#####

#####, #####

SJ#####

#####/#/

S1 PS / SR, ESD, #####, HRO
EU 35-48 / UK 3.0-13.0 / US 3.0-13.5
JPN 21.5-31.5 / KOR 230-315
0.510 kg
ASTM F2413:2018
EN ISO 20345:2022



#####



#####



#####100#####



####



BLK



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

#####:
##, #####, ##, #####

#####:
##, #####

#####:
#####

####		####	##	EN ISO 20345
####	#####, ######			
	#####	mg/cm ² /h	1.2	# 0.8
	#####	mg/cm ²	21	# 15
##	####			
	#####	mg/cm ² /h	34.59	# 2
	#####	mg/cm ²	277	# 20
#####	SJ#####			
	#####	####	Dry 25600 cycles/Wet 12800 cycles	25600/12800
#####	#####/####			
	#####	mm ³	Relative volume loss: 140mm ³ (Density:1.21)	# 150
	##### - #####NaLS - #####	####	0.48	# 0.31
	##### - #####NaLS - #####	####	0.48	# 0.36
	SR ### - ##### - #####	####	0.36	# 0.19
	SR##### - ##### - #####	####	0.36	# 0.22
	#####	####	658	0.1 - 1000
	ESD#	####	19.1	0.1 - 100
	#####	J	25	# 20
#####	#####			
	#####100J#	mm	N/A	N/A
	#####10kN#####	mm	N/A	N/A
	#####200J#	mm	15.5	# 14
	#####15kN#	mm	22.0	# 14

#####:

#####Safety Jogger #####



**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the top 1% by EcoVadis for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com