

##:
####, ###, ##, ##

##:
##, ### ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	##, ##			
	##: ### ###	mg/cm²/h	1.2	# 0.8
	##: ### ##	mg/cm²	21	# 15
## ##	##			
	##: ### ###	mg/cm²/h	34.59	# 2
	##: ### ##	mg/cm²	277	# 20
##	SJ ### # ###			
	###: ####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
## #	###/##			
	#### ####(## ##)	mm³	Relative volume loss: 140mm³ (Density:1.21)	# 150
	## ### ## - ### + NaLS - ## ### #####	##	0.48	# 0.31
	## ### ## - ### + NaLS - ## ## ###	##	0.48	# 0.36
	SR ### ## - ### + ##### - ##### ### ##	##	0.36	# 0.19
	SR ### ## - ### + ##### - ## ## ###	##	0.36	# 0.22
	### ## #	###	658	0.1 - 1000
	ESD #	###	19.1	0.1 - 100
	##### ## ##	J	25	# 20
Top	##			
	##### ## ##(## # ## 100J)	mm	N/A	N/A
	##### ## ##(## # ## ## 10kN)	mm	N/A	N/A
	##### ## ##(## # ## 200J)	mm	15.5	# 14
	### ## ## ##(## # ## ## 15kN)	mm	22.0	# 14

##:

##, ## ## ##### ## ## #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ##### ## ##### ##### ## ##.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com