



MODULO S1PS SANDAL

MODULOS1PS

#####

MODULO#####
ESD#####
#####

SJ####

#PU##PU

S1 PS / SR, SC, ESD, #####
EU 35-48 / UK 3.0-13.0 / US 3.0-13.5
JPN 21.5-31.5 / KOR 230-315
0.550 kg
ASTM F2413:2018
EN ISO 20345:2022+A1:2024
IS 15298 (Part 2): 2016



#####100#####



#####SC#

###




(SR)
#####SRA+SRB=SRC#####
#####SR#####



#####



#####



#####



GRY



112



BLK

#####:
##, #####, ##, #####

#####:
####, #####

#####:
#####

####		####	##	EN ISO 20345
####	#####			
	#####	mg/cm ² /h	8.20	# 0.8
	#####	mg/cm ²	68	# 15
##	####			
	#####	mg/cm ² /h	60.62	# 2
	#####	mg/cm ²	485	# 20
####	SJ#####			
	#####	####	Dry 25600 cycles/Wet 12800 cycles	25600/12800
#####	###PU/###PU			
	#####	mm ³	127mm ³ (Density:1.09g/ cm ³)	# 150
	##### - #####NaLS - #####	####	0.33	# 0.31
	##### - #####NaLS - #####	####	0.42	# 0.36
	SR ### - ##### - #####	####	0.22	# 0.19
	SR##### - ##### - #####	####	0.25	# 0.22
	#####	####	31.5	0.1 - 100
	ESD#	####	21	0.1 - 100
	#####	J	31	# 20
#####	#####			
	#####100J#	mm	N/A	N/A
	#####10kN#####	mm	N/A	N/A
	#####200J#	mm	15.5	# 14
	#####15kN#	mm	21.0	# 14

#####:

#####Safety Jogger #####



**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com