

#

MODULOS1PS

#####

```
##### MODULO# ##### ## ## ##### #####. # ## ##
##, ## ##, ## ##, ESD, ## ##, ## ## # ## ## #####. ## ##
#####.
```

## ##	#####
## ##	##
##	SJ # ##
##	## ## ##
## #	### PU/### PU
Top	####
#####	S1 PS / SR, SC, ESD, FO
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.550 kg
####	ASTM F2413:2018 EN ISO 20345:2022+A1:2024 IS 15298 (Part 2): 2016



```
## ## ##
### ## ## ##### ## ## ##.
### ## ## 100% ## ## ##### ##.
```



```
### #(SC)
### ## # # ## ### ### ###
#### ##### ## ## ### ## ##
#### ## ### #####.
```




```
### ##
### ### ### ### ### ## # ### #####
### #####.
```



```
##
#### #### ##### ##### #####.
```



```
### ##(SR)
### ##### SRA+SRB=SRC ###
#####. SR# ### ##### ### ##
## ##### #####.
```



```
## ##
### ## ##### ## #####
#####. ## ## ##### ## ## # #####
## ##### ## #####.
```



112



GRY



BLK

##:
####, ###, ##, ##

##:
##, ## #####

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	#####			
	##: ### ###	mg/cm²/h	8.20	# 0.8
	##: ### ##	mg/cm²	68	# 15
## ##	##			
	##: ### ###	mg/cm²/h	60.62	# 2
	##: ### ##	mg/cm²	485	# 20
##	SJ # ##			
	###: ####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
## #	### PU/### PU			
	#### #####(## ##)	mm³	127mm³ (Density:1.09g/cm³)	# 150
	## ### ## - ### + NaLS - ## ### #####	##	0.33	# 0.31
	## ### ## - ### + NaLS - ## ## ###	##	0.42	# 0.36
	SR ### ## - ### + ##### - ##### ### ##	##	0.22	# 0.19
	SR ### ## - ### + ##### - ## ## ###	##	0.25	# 0.22
	### ## #	###	31.5	0.1 - 1000
	ESD #	###	21	0.1 - 100
	##### ## ##	J	31	# 20
Top	####			
	#### ## ##(## # ## 100J)	mm	N/A	N/A
	#### ## ##(## # ## ## 10kN)	mm	N/A	N/A
	#### ## ##(## # ## 200J)	mm	15.5	# 14
	### ## ## ##(## # ## ## 15kN)	mm	21.0	# 14

##:

#####, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ##### ## ##### ##### ## # #####.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com