



#

MODULO S1PS SANDAL

MODULOS1PS

#

##, MODULO# #### ## # #### # #### #. # ## ##
##, ## ##, ## ##, ESD, ## ##, ## # # ## # ## # #### #. ## ##
#####.

## #	#####
## #	##
##	SJ # #
##	## # #
## #	### PU/### PU
Top	####
####	S1 PS / SR, SC, ESD, FO
## #	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## #	0.550 kg
###	ASTM F2413:2018 EN ISO 20345:2022+A1:2024 IS 15298 (Part 2): 2016



#.
100% # # #### # #.



#(SC)

#.




#(SR)
SRA+SRB=SRC ##
#. SR# # # # # # # # # #
#.



#.



#.



#. ## # # # # # # # # # #
#.



BLK



GRY



112

##:
####, ###, ##, ##

##:
##, ## #####

##:
#####. ### ##### ## ##### ### ##.

	##	## ##	##	EN ISO 20345
## ##	#####			
	##: ### ###	mg/cm²/h	8.20	# 0.8
	##: ### ##	mg/cm²	68	# 15
## ##	##			
	##: ### ###	mg/cm²/h	60.62	# 2
	##: ### ##	mg/cm²	485	# 20
##	SJ # ##			
	###: ####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
## #	### PU/### PU			
	#### #####(## ##)	mm³	127mm³ (Density:1.09g/cm³)	# 150
	## ### ## - ### + NaLS - ## ### #####	##	0.33	# 0.31
	## ### ## - ### + NaLS - ## ## ###	##	0.42	# 0.36
	SR ### ## - ### + ##### - ##### ### ##	##	0.22	# 0.19
	SR ### ## - ### + ##### - ## ## ###	##	0.25	# 0.22
	### ## #	###	31.5	0.1 - 1000
	ESD #	###	21	0.1 - 100
	##### ## ##	J	31	# 20
Top	####			
	#### ## ##(## # ## 100J)	mm	N/A	N/A
	#### ## ##(## # ## ## 10kN)	mm	N/A	N/A
	#### ## ##(## # ## 200J)	mm	15.5	# 14
	### ## ## ##(## # ## ## 15kN)	mm	21.0	# 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ##### ## ##### ##### ## # #####.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com