

Medium

## MODULO S3S MID TLS

MODULOS3MT

**Super comfortable vegan safety mid cut sneaker with TLS closing**

**Comfort that lasts.** MODULO is the ultimate choice for both men and women who demand excellence from their safety footwear. This safety shoe offers an array of key features, such as slip resistance, a breathable design, comfortable footbed, ESD, lightweight midsole and toe cap & much more. Made from vegan materials.

|               |   |
|---------------|---|
| Upper         | Microfiber  |
| Lining        | Mesh  |
| Footbed       | SJ foam footbed   |
| Midsole       | Anti-puncture Textile   |
| Outsole       | BASF PU/BASF PU   |
| Toecap        | Nano Carbon   |
| Category      | S3S / SR, SC, ESD, CI, FO   |
| Size range    | EU 35-50 / UK 3.0-14.0 / US 3.0-15.0<br>JPN 21.5-33.0 / KOR 230-330 |
| Sample weight | 0.500 kg  |
| Norms         | ASTM F2413:2018<br>EN ISO 20345:2022<br>IS 15298 (Part 2): 2016     |



GRY



BLK



**Puncture resistant lightweight**  
Metal free, super flexible and ultralight puncture resistant midsole. Covers 100% of the bottom area of the last, no thermal conductivity.

**Scuff Cap (SC)**  
Separately tested material to cover the toe cap area to reduce abrasion of the upper material (e.g. during kneeling operations) and extend usability of the safety shoe.

**Slip resistance (SR)**  
Replaces the previously used term of SRA+SRB=SRC. SR means the slip test has been executed on tiles contaminated with soap and with oil.

**Vegan**  
Uses or contains no animal products.

**TLS (Twist Lock System)**  
Safety Jogger's innovative TLS closure allows you to quickly tighten and loosen your safety footwear with one hand and under any conditions, even when you are wearing safety gloves. TLS ensures a fast, safe and easy precision fit that offers enhanced comfort and enables you to perform at your best.

**Metal free**  
Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.

**Industries:**

Assembly, Automotive, Catering, Cleaning, Logistics, Industry

**Environments:**

Dry environment, Extreme slippery surfaces, Wet environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

|                | Description  | Measure unit          | Result  | EN ISO 20345 |
|----------------|--|-----------------------|---|--------------|
| <b>Upper</b>   | <b>Microfiber</b>  |                       |   |              |
|                | Upper: permeability to water vapor                               | mg/cm <sup>2</sup> /h | 8.20  | ≥ 0.8        |
|                | Upper: water vapor coefficient                                   | mg/cm <sup>2</sup>    | 68  | ≥ 15         |
| <b>Lining</b>  | <b>Mesh</b>  |                       |   |              |
|                | Lining: permeability to water vapor                              | mg/cm <sup>2</sup> /h | 60.62   | ≥ 2          |
|                | Lining: water vapor coefficient                                  | mg/cm <sup>2</sup>    | 485   | ≥ 20         |
| <b>Footbed</b> | <b>SJ foam footbed</b>   |                       |   |              |
|                | Footbed: abrasion resistance (dry/wet) (cycles)                  | cycles                | Dry 25600<br>cycles/Wet<br>12800 cycles                     | 25600/12800  |
| <b>Outsole</b> | <b>BASF PU/BASF PU</b>   |                       |   |              |
|                | Outsole abrasion resistance (volume loss)                        | mm <sup>3</sup>       | 127mm <sup>3</sup><br>(Density: 1.09g/<br>cm <sup>3</sup> ) | ≤ 150        |
|                | Basic Slip resistance - Ceramic + NaLS - Forward heel slip       | friction              | 0.33  | ≥ 0.31       |
|                | Basic Slip resistance - Ceramic + NaLS - Backward forepart slip  | friction              | 0.42  | ≥ 0.36       |
|                | SR Slip resistance - Ceramic + glycerin - Forward heel slip      | friction              | 0.22  | ≥ 0.19       |
|                | SR Slip resistance - Ceramic + glycerin - Backward forepart slip | friction              | 0.25  | ≥ 0.22       |
|                | Antistatic value   | MegaOhm               | 31.5  | 0.1 - 1000   |
|                | ESD value  | MegaOhm               | 21  | 0.1 - 100    |
|                | Heel energy absorption   | J                     | 31  | ≥ 20         |
| <b>Toecap</b>  | <b>Nano Carbon</b>   |                       |   |              |
|                | Impact resistance toecap (clearance after impact 100J)           | mm                    | N/A   | N/A          |
|                | Compression resistance toecap (clearance after compression 10kN) | mm                    | N/A   | N/A          |
|                | Impact resistance toecap (clearance after impact 200J)           | mm                    | 15.5  | ≥ 14         |
|                | Compression resistance toecap (clearance after compression 15kN) | mm                    | 21.0  | ≥ 14         |

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.