

Light

ORGANIC S1 P

ORGANIC: Ultimate Dry Work Environment Footwear

Safety Jogger's ORGANIC low-cut safety shoes provide optimum protection in dry environments with S1P protection, SR slip resistance, steel toecap and midsole, and antistatic properties. The breathable leather upper ensures comfort and durability.

| | |
|---------------|--|
| Upper | Suede Leather |
| Lining | Mesh |
| Footbed | SJ foam footbed |
| Midsole | Steel |
| Outsole | PU/PU |
| Toecap | Steel |
| Category | S1 P / SRC |
| Size range | EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 JPN 21.5-26.5 / KOR 230-270 |
| Sample weight | 0.490 kg |
| Norms | ASTM F2413:2018 EN ISO 20345:2011 |



DGR



S1P

You work in dry environments, no risk of water/liquid sprays, and you need protection for your toes, protection against perforation, and a good breathability? Then you need S1P safety footwear.



Steel toecap

Robust metal support to protect the feet of the wearer against falling or rolling objects.



Steel midsole

Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



Antistatic

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

Industries:

Automotive, Cleaning, Construction, Logistics

Environments:

Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20345 |
|---------|--|--------------|-------------|--------------|
| Upper | Suede Leather | | | |
| | Upper: permeability to water vapor | mg/cm²/h | 6.9 | # 0.8 |
| | Upper: water vapor coefficient | mg/cm² | 61.1 | # 15 |
| Lining | Mesh | | | |
| | Lining: permeability to water vapor | mg/cm²/h | 60.5 | # 2 |
| | Lining: water vapor coefficient | mg/cm² | 484.1 | # 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | PU/PU | | | |
| | Outsole abrasion resistance (volume loss) | mm³ | 29.1 | # 150 |
| | Outsole slip resistance SRA: heel | friction | 0.40 | # 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.39 | # 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.15 | # 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.20 | # 0.18 |
| | Antistatic value | MegaOhm | 189.9 | 0.1 - 1000 |
| | ESD value | MegaOhm | N/A | 0.1 - 100 |
| | Heel energy absorption | J | 27 | # 20 |
| Toecap | Steel | | | |
| | Impact resistance toecap (clearance after impact 100J) | mm | N/A | N/A |
| | Compression resistance toecap (clearance after compression 10kN) | mm | N/A | N/A |
| | Impact resistance toecap (clearance after impact 200J) | mm | 14.0 | # 14 |
| | Compression resistance toecap (clearance after compression 15kN) | mm | 14.5 | # 14 |

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com